Product data sheet
Characteristics

LC1D65AE7C
Contactor, TeSys Deca, 3P(3 NO), AC-3/ AC-3e, 0 to 440V, 65A, 48VAC 50/60Hz coil, Everlink terminal



Commercial status
End of Commercialisation :

⚠ End of Commercialisation

Main

Range	TeSys Deca
Range of product	TeSys Deca
Product or component type	Contactor
Device short name	LC1D
Contactor application	Motor control Resistive load
Utilisation category	AC-4 AC-1 AC-3 AC-3e
Poles description	3P
[Ue] rated operational voltage	Power circuit: <= 690 V AC 25...400 Hz Power circuit: <= 300 V DC
[Ie] rated operational current	80 A (at <60 °C) at <= 440 V AC AC-1 for power circuit 65 A (at <60 °C) at <= 440 V AC AC-3 for power circuit 65 A (at <60 °C) at <= 440 V AC AC-3e for power circuit
[Uc] control circuit voltage	48 V AC 50/60 Hz

Complementary

Motor power kW	37 KW at 500 V AC 50/60 Hz (AC-3) 18.5 KW at 220/240 V AC 50/60 Hz (AC-3) 30 KW at 380/400 V AC 50/60 Hz (AC-3) 37 KW at 660/690 V AC 50/60 Hz (AC-3) 37 KW at 415/440 V AC 50/60 Hz (AC-3) 37 KW at 500 V AC 50/60 Hz (AC-3e) 18.5 KW at 220/240 V AC 50/60 Hz (AC-3e) 30 KW at 380/400 V AC 50/60 Hz (AC-3e) 37 KW at 660/690 V AC 50/60 Hz (AC-3e) 37 KW at 415/440 V AC 50/60 Hz (AC-3e)
Compatibility code	LC1D
Pole contact composition	3 NO
Protective cover	With
[Ith] conventional free air thermal current	10 A (at 60 °C) for signalling circuit 80 A (at 60 °C) for power circuit
[Icw] rated short-time withstand current	520 A 40 °C - 10 s for power circuit 900 A 40 °C - 1 s for power circuit 110 A 40 °C - 10 min for power circuit 260 A 40 °C - 1 min for power circuit 100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit

Associated fuse rating	10 A gG for signalling circuit conforming to IEC 60947-5-1 125 A gG at <= 690 V coordination type 2 for power circuit 160 A gG at <= 690 V coordination type 1 for power circuit
Average impedance	1.5 MOhm - Ith 80 A 50 Hz for power circuit
[Ui] rated insulation voltage	Power circuit: 690 V conforming to IEC 60947-4-1 Signalling circuit: 690 V conforming to IEC 60947-1
Overvoltage category	III
Pollution degree	3
[Uimp] rated impulse withstand voltage	6 KV conforming to IEC 60947
Safety reliability level	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1
Mechanical durability	6 Mcycles
Electrical durability	1.5 Mcycles 65 A AC-3 at Ue <= 440 V 2.5 Mcycles 42 A AC-3 at Ue 660/690 V 1.3 Mcycles 80 A AC-1 at Ue <= 440 V 1.5 Mcycles 65 A AC-3e at Ue <= 440 V 2.5 Mcycles 42 A AC-3e at Ue 660/690 V
Control circuit type	AC at 50/60 Hz
Coil technology	Without built-in suppressor module
Control circuit voltage limits	0.3...0.6 Uc (-40…60 °C):drop-out 50/60 Hz 0.8...1.1 Uc (-40…60 °C):operational 50 Hz 0.85...1.1 Uc (-40…60 °C):operational 60 Hz
Inrush power in VA	140 VA 60 Hz cos phi 0.75 (at 20 °C) 160 VA 50 Hz cos phi 0.75 (at 20 °C)
Hold-in power consumption in VA	13 VA 60 Hz cos phi 0.3 (at 20 °C) 15 VA 50 Hz cos phi 0.3 (at 20 °C)
Operating time	4...19 ms opening 12...26 ms closing
Connections - terminals	Power circuit: EverLink BTR screw connectors 1 1…35 mm² - external diameter: 16.5 mm - cable s Power circuit: EverLink BTR screw connectors 2 1…25 mm² - external diameter: 16.5 mm - cable Power circuit: EverLink BTR screw connectors 2 1…35 mm² - external diameter: 16.5 mm - cable Power circuit: EverLink BTR screw connectors 1…25 mm² - external diameter: 16.5 mm - cable st Power circuit: EverLink BTR screw connectors 1…35 mm² - external diameter: 16.5 mm - cable st Power circuit: EverLink BTR screw connectors 1…25 mm² - external diameter: 16.5 mm - cable st Control circuit: screw clamp terminals 1…4 mm² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 1…2.5 mm² - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1…4 mm² - cable stiffness: solid without cable end
Tightening torque	Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 Power circuit: 8 N.m - on EverLink BTR screw connectors - cable 35 mm² hexagonal screw head 4 Power circuit: 6 N.m - on screw clamp terminals hexagonal screw head 10 mm M6 Power circuit: 5 N.m - on EverLink BTR screw connectors - cable 1…25 mm² hexagonal screw he Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver pozidriv No 2
Auxiliary contacts type	Type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 type mirror contact 1 NC conforming to IEC 60947-4-1
Auxiliary contact composition	1 NO + 1 NC
Signalling circuit frequency	25...400 Hz
Minimum switching current	5 MA for signalling circuit
Insulation resistance	> 10 MOhm for signalling circuit
Non-overlap time	1.5 Ms on de-energisation between NC and NO contact 1.5 Ms on energisation between NC and NO contact
Mounting support	Rail Plate

Environment

Standards	IEC 60947-1 IEC 60947-4-1 GB/T 14048.4
Product certifications	CE[RETURN]UKCA[RETURN]CCC
IP degree of protection	IP2X front face for main circuit conforming to IEC 60529 IP2X front face for coil circuit conforming to IEC 60529
Protective treatment	TH conforming to IEC 60068-2-30
Permissible ambient air temperature around the device	-40…60 °C operation 60…70 °C with derating -60…80 °C storage
Operating altitude	3000 m without derating

Fire resistance	850 °C conforming to IEC 60695-2-11
Mechanical robustness	Vibrations contactor open (2 Gn, 5...300 Hz) conforming to IEC 60068-2-6 Vibrations contactor closed (4 Gn, 5...300 Hz) conforming to IEC 60068-2-6 Shocks 11 ms contactor open (10 Gn) conforming to IEC 60068-2-27 Shocks 11 ms contactor closed (15 gn) conforming to IEC 60068-2-27
Height	122 Mm
Width	55 Mm
Depth	120 Mm
Net weight	0.86 Kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.6 Cm
Package 1 Width	14.3 Cm
Package 1 Length	15.6 Cm
Package 1 Weight	983.72 G
Unit Type of Package 2	S02
Number of Units in Package 2	10
Package 2 Height	15.0 Cm
Package 2 Width	30.0 Cm
Package 2 Length	40.0 Cm
Package 2 Weight	9.994 Kg
Unit Type of Package 3	PAL
Number of Units in Package 3	160
Package 3 Height	75.0 Cm
Package 3 Width	60.0 Cm
Package 3 Length	80.0 Cm
Package 3 Weight	163.68 Kg

Offer Sustainability

Recyclability potential, in %	62
Total lifecycle Carbon footprint	83 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	4.251993973978119
Carbon footprint of the manufacturing phase [A1 to A3]	4 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.39860579699531423
Carbon footprint of the distribution phase [A4]	0.4 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.05192179391361554
Carbon footprint of the installation phase [A5]	0.1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	76.62394170546868
Carbon footprint of the use phase [B2, B3, B4, B6]	77 kg CO2 eq.
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	Yes
Carbon footprint of the end-of-life phase [C1 to C4]	1.2081206897335017
Carbon footprint of the end-of-life phase [C1 to C4]	1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	83
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
End of life manual availability	End Of Life Information
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status :	End of commerc. - Block