# Product data sheet
## Characteristics

# LC1D95MD
Contactor, TeSys Deca, 3P(3NO), AC-3/AC-3e, <=440V, 95A, 220V DC standard coil, screw clamp terminals



## Main

| | |
|---|---|
| Range | TeSys |
| Range of product | TeSys Deca Advanced |
| Product or component type | Contactor |
| Device short name | LC1D |
| Contactor application | Motor control<br>Resistive load |
| Utilisation category | AC-3<br>AC-3e<br>AC-1<br>AC-4 |
| Poles description | 3P |
| [Ue] rated operational voltage | Power circuit: <= 690 V AC 25...400 Hz |
| [Ie] rated operational current | 95 A (at <60 °C) at <= 440 V AC-3 for power circuit<br>125 A (at <60 °C) at <= 1000 V AC-1 for power circuit<br>95 A (at <60 °C) at <= 440 V AC-3e for power circuit |
| [Uc] control circuit voltage | 220 V DC |

## Complementary

| | |
|---|---|
| Motor power kW | 25 KW at 220/230 V AC 50/60 Hz (AC-3)<br>45 KW at 380/400 V AC 50/60 Hz (AC-3)<br>45 KW at 415/440 V AC 50/60 Hz (AC-3)<br>55 KW at 500 V AC 50/60 Hz (AC-3)<br>45 KW at 660/690 V AC 50/60 Hz (AC-3)<br>25 KW at 220/230 V AC 50/60 Hz (AC-3e)<br>45 KW at 380/400 V AC 50/60 Hz (AC-3e)<br>45 KW at 415/440 V AC 50/60 Hz (AC-3e)<br>55 KW at 500 V AC 50/60 Hz (AC-3e)<br>45 KW at 660/690 V AC 50/60 Hz (AC-3e)<br>15 KW at 400 V AC 50/60 Hz (AC-4) |
| Motor power hp | 7.5 Hp at 120 V AC 60 Hz for 1 phase motors<br>15 Hp at 230/240 V AC 60 Hz for 1 phase motors<br>30 Hp at 200/208 V AC 60 Hz for 3 phases motors<br>30 Hp at 230/240 V AC 60 Hz for 3 phases motors<br>60 Hp at 460/480 V AC 60 Hz for 3 phases motors<br>60 Hp at 575/600 V AC 60 Hz for 3 phases motors |
| Compatibility code | LC1D |
| Pole contact composition | 3 NO |
| Protective cover | With |
| [Ith] conventional free air thermal current | 10 A (at 60 °C) for signalling circuit<br>125 A (at 60 °C) for power circuit |
| Irms rated making capacity | 1100 A at 440 V AC for power circuit conforming to IEC 60947<br>140 A AC for signalling circuit conforming to IEC 60947-5-1<br>250 A DC for signalling circuit conforming to IEC 60947-5-1 |

| | |
|---|---|
| Rated breaking capacity | 1100 A at 440 V for power circuit conforming to IEC 60947 |
| [Icw] rated short-time withstand current | 1100 A 40 °C - 1 s for power circuit<br>800 A 40 °C - 10 s for power circuit<br>400 A 40 °C - 1 min for power circuit<br>135 A 40 °C - 10 min for power circuit<br>140 A - 100 ms for signalling circuit<br>120 A - 500 ms for signalling circuit<br>100 A - 1 s for signalling circuit |
| Associated fuse rating | 10 A gG for signalling circuit conforming to IEC 60947-5-1<br>200 A gG at <= 690 V coordination type 1 for power circuit<br>160 A gG at <= 690 V coordination type 2 for power circuit |
| Average impedance | 0.8 MOhm - Ith 125 A 50 Hz for power circuit |
| Power dissipation per pole | 12.5 W AC-1<br>7.2 W AC-3<br>7.2 W AC-3e |
| [Ui] rated insulation voltage | Power circuit: 1000 V conforming to IEC 60947-4-1<br>Signalling circuit: 690 V conforming to IEC 60947-1 |
| Overvoltage category | III |
| Pollution degree | 3 |
| [Uimp] rated impulse withstand voltage | 8 KV conforming to IEC 60947 |
| Safety reliability level | B10d = 1.3 Mcycles contactor with nominal load conforming to EN/ISO 13849-1<br>B10d = 20 Mcycles contactor with mechanical load conforming to EN/ISO 13849-1 |
| Mechanical durability | 10 Mcycles |
| Electrical durability | 1.2 Mcycles 95 A AC-3<br>1.3 Mcycles 125 A AC-1<br>1.2 Mcycles 95 A AC-3e |
| Control circuit type | DC standard |
| Coil technology | Without built-in suppressor module |
| Control circuit voltage limits | 0.1...0.3 Uc (-40…70 °C):drop-out DC<br>0.85...1.1 Uc (-40…55 °C):operational DC<br>1...1.1 Uc (55…70 °C):operational DC |
| Inrush power in W | 22 W (at 20 °C) |
| Hold-in power consumption in W | 22 W at 20 °C |
| Operating time | 95...130 ms closing<br>20...35 ms opening |
| Time constant | 75 Ms |
| Maximum operating rate | 3600 Cyc/H at 60 °C |
| Connections - terminals | Control circuit: screw clamp terminals 2 1…2.5 mm² - cable stiffness: flexible with cable end<br>Control circuit: screw clamp terminals 1 1…2.5 mm² - cable stiffness: flexible with cable end<br>Control circuit: screw clamp terminals 1 1…4 mm² - cable stiffness: flexible without cable end<br>Control circuit: screw clamp terminals 2 1…4 mm² - cable stiffness: flexible without cable end<br>Control circuit: screw clamp terminals 1 1…4 mm² - cable stiffness: solid without cable end<br>Control circuit: screw clamp terminals 2 1…4 mm² - cable stiffness: solid without cable end<br>Power circuit: connector 1 4…50 mm² - cable stiffness: flexible without cable end<br>Power circuit: connector 2 4…25 mm² - cable stiffness: flexible without cable end<br>Power circuit: connector 1 4…50 mm² - cable stiffness: flexible with cable end<br>Power circuit: connector 2 4…16 mm² - cable stiffness: flexible with cable end<br>Power circuit: connector 1 4…50 mm² - cable stiffness: solid without cable end<br>Power circuit: connector 2 4…25 mm² - cable stiffness: solid without cable end |
| Tightening torque | Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm<br>Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver Philips No 2<br>Power circuit: 12 N.m - on connector - with screwdriver flat Ø 6 to Ø 8 mm<br>Power circuit: 12 N.m - on connector hexagonal screw head 4 mm<br>Control circuit: 1.2 N.m - on screw clamp terminals - with screwdriver pozidriv No 2 |
| Auxiliary contact composition | 1 NO + 1 NC |
| Auxiliary contacts type | Type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1<br>type mirror contact 1 NC conforming to IEC 60947-4-1 |
| Signalling circuit frequency | 25...400 Hz |
| Minimum switching voltage | 17 V for signalling circuit |
| Minimum switching current | 5 MA for signalling circuit |
| Insulation resistance | > 10 MOhm for signalling circuit |
| Non-overlap time | 1.5 Ms on de-energisation between NC and NO contact<br>1.5 Ms on energisation between NC and NO contact |
| Mounting support | Plate<br>Rail |

## Environment

| | |
|---|---|
| Standards | EN 60947-4-1<br>EN 60947-5-1<br>IEC 60947-4-1<br>IEC 60947-5-1<br>CSA C22.2 No 14<br>UL 60947-4-1<br>IEC 60335-2-40:Annex JJ<br>UL 60335-2-40:Annex JJ<br>IEC 60335-1:Clause 30.2 |
| Product certifications | IECEE CB Scheme[RETURN]CCC[RETURN]EAC[RETURN]LROS (Lloyds register of shipping |
| IP degree of protection | IP20 front face conforming to IEC 60529 |
| Protective treatment | TH conforming to IEC 60068-2-30 |
| Climatic withstand | Conforming to IACS E10 exposure to damp heat |
| Permissible ambient air temperature around the device | -40…60 °C<br>60…70 °C with derating |
| Operating altitude | 0...3000 m |
| Fire resistance | 850 °C conforming to IEC 60695-2-1 |
| Flame retardance | V1 conforming to UL 94 |
| Mechanical robustness | Vibrations contactor open (2 Gn, 5...300 Hz)<br>Shocks contactor open (8 Gn for 11 ms)<br>Vibrations contactor closed (3 Gn, 5...300 Hz)<br>Shocks contactor closed (10 Gn for 11 ms) |
| Height | 127 Mm |
| Width | 85 Mm |
| Depth | 186 Mm |
| Net weight | 2.61 Kg |

## Packing Units

| | |
|---|---|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 21.0 Cm |
| Package 1 Width | 10.0 Cm |
| Package 1 Length | 14.0 Cm |
| Package 1 Weight | 2.644 Kg |

## Offer Sustainability

| | |
|---|---|
| Recyclability potential, in % | 76 |
| Total lifecycle Carbon footprint | 185 kg CO2 eq. |
| Carbon footprint of the manufacturing phase [A1 to A3] | 17.320171625437503 |
| Carbon footprint of the manufacturing phase [A1 to A3] | 17 kg CO2 eq. |
| Carbon footprint of the distribution phase [A4] | 0.3416810635410429 |
| Carbon footprint of the distribution phase [A4] | 0.3 kg CO2 eq. |
| Carbon footprint of the installation phase [A5] | 0.4899056242009124 |
| Carbon footprint of the installation phase [A5] | 0.5 kg CO2 eq. |
| Carbon footprint of the use phase [B2, B3, B4, B6] | 160.36942028985501 |
| REACh free of SVHC | Yes |
| Carbon footprint of the use phase [B2, B3, B4, B6] | 160 kg CO2 eq. |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| Sustainable packaging | Yes |
| Carbon footprint of the end-of-life phase [C1 to C4] | 6.461453621222985 |
| Carbon footprint of the end-of-life phase [C1 to C4] | 6 kg CO2 eq. |
| Environmental Disclosure | Product Environmental Profile |
| Total lifecycle Carbon footprint | 185 |
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | Yes |

| | |
|---|---|
| REACh Regulation | Free of Substances of Very High Concern above the threshold |
| EU RoHS Directive | Compliant |
| PVC free | Yes |
| End of life manual availability | No need of specific recycling operations |
| Take-back | No |
| WEEE Label | The product must be disposed on European Union markets following specific waste collection and |

## Contractual warranty

| | |
|---|---|
| Warranty (in months) | 18 |

Product Life Status : Commercialised