# Product data sheet
## Characteristics

# LC1DT32F7C
Contactor, TeSys Deca, 4P(4NO), AC-1, <= 440V, 32A, 110V AC 50/60Hz coil, screw terminal



⚠ End of Commercialisation

## Commercial status
End of Commercialisation :

## Main

| | |
|---|---|
| Range | TeSys Deca |
| Range of product | TeSys Deca |
| Product or component type | Contactor |
| Device short name | LC1D |
| Contactor application | Motor control<br>Resistive load |
| Utilisation category | AC-1<br>AC-3<br>AC-3e<br>AC-4 |
| Poles description | 4P |
| [Ue] rated operational voltage | Power circuit: <= 690 V AC 25...400 Hz<br>Power circuit: <= 225 V DC |
| [Ie] rated operational current | 32 A (at <60 °C) at <= 440 V AC AC-1 for power circuit |
| [Uc] control circuit voltage | 110 V AC 50/60 Hz |

## Complementary

| | |
|---|---|
| Compatibility code | LC1D |
| Pole contact composition | 4 NO |
| Protective cover | With |
| [Ith] conventional free air thermal current | 10 A (at 60 °C) for signalling circuit<br>32 A (at 60 °C) for power circuit |
| [Icw] rated short-time withstand current | 145 A 40 °C - 10 s for power circuit<br>240 A 40 °C - 1 s for power circuit<br>40 A 40 °C - 10 min for power circuit<br>84 A 40 °C - 1 min for power circuit<br>100 A - 1 s for signalling circuit<br>120 A - 500 ms for signalling circuit<br>140 A - 100 ms for signalling circuit |
| Associated fuse rating | 10 A gG for signalling circuit conforming to IEC 60947-5-1<br>50 A gG at <= 690 V coordination type 1 for power circuit<br>35 A gG at <= 690 V coordination type 2 for power circuit |
| Average impedance | 2.5 MOhm - Ith 32 A 50 Hz for power circuit |
| [Ui] rated insulation voltage | Power circuit: 690 V conforming to IEC 60947-4-1<br>Signalling circuit: 690 V conforming to IEC 60947-1 |
| Overvoltage category | III |
| Pollution degree | 3 |
| [Uimp] rated impulse withstand voltage | 6 KV conforming to IEC 60947 |

| | |
|---|---|
| Safety reliability level | B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1<br>B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1 |
| Mechanical durability | 15 Mcycles |
| Electrical durability | 1 Mcycles 32 A AC-1 at Ue <= 440 V |
| Control circuit type | AC at 50/60 Hz |
| Coil technology | Without built-in suppressor module |
| Control circuit voltage limits | 0.3...0.6 Uc (-40…60 °C):drop-out 50/60 Hz<br>0.8...1.1 Uc (-40…60 °C):operational 50 Hz<br>0.85...1.1 Uc (-40…60 °C):operational 60 Hz |
| Inrush power in VA | 70 VA 60 Hz cos phi 0.75 (at 20 °C)<br>70 VA 50 Hz cos phi 0.75 (at 20 °C) |
| Hold-in power consumption in VA | 6 VA 60 Hz cos phi 0.3 (at 20 °C)<br>7 VA 50 Hz cos phi 0.3 (at 20 °C) |
| Operating time | 12...22 ms closing<br>4...19 ms opening |
| Connections - terminals | Control circuit: screw clamp terminals 1 1…4 mm² - cable stiffness: flexible without cable end<br>Control circuit: screw clamp terminals 2 1…4 mm² - cable stiffness: flexible without cable end<br>Control circuit: screw clamp terminals 1 1…4 mm² - cable stiffness: flexible with cable end<br>Control circuit: screw clamp terminals 2 1…2.5 mm² - cable stiffness: flexible with cable end<br>Control circuit: screw clamp terminals 1 1…4 mm² - cable stiffness: solid without cable end<br>Control circuit: screw clamp terminals 2 1…4 mm² - cable stiffness: solid without cable end<br>Power circuit: connector 1 2.5…10 mm² - external diameter: 8 mm - cable stiffness: flexible withou<br>Power circuit: connector 2 2.5…10 mm² - external diameter: 8 mm - cable stiffness: flexible withou<br>Power circuit: connector 1 2.5…10 mm² - external diameter: 8 mm - cable stiffness: flexible with ca<br>Power circuit: connector 2 2.5…10 mm² - external diameter: 8 mm - cable stiffness: flexible with ca<br>Power circuit: connector 1 2.5…16 mm² - external diameter: 8 mm - cable stiffness: solid without c<br>Power circuit: connector 2 2.5…16 mm² - external diameter: 8 mm - cable stiffness: solid without c<br>Power circuit: screw connection |
| Tightening torque | Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm<br>Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2<br>Power circuit: 1.8 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm<br>Power circuit: 1.8 N.m - on screw clamp terminals - with screwdriver Philips No 2<br>Power circuit: 1.8 N.m - on cable connector - with screwdriver flat Ø 6 mm M3.5<br>Power circuit: 1.8 N.m - on cable connector - with screwdriver Philips No 2 M3.5<br>Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver pozidriv No 2<br>Power circuit: 1.8 N.m - on screw clamp terminals - with screwdriver pozidriv No 2 |
| Auxiliary contacts type | Type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1<br>type mirror contact 1 NC conforming to IEC 60947-4-1 |
| Auxiliary contact composition | 1 NO + 1 NC |
| Signalling circuit frequency | 25...400 Hz |
| Minimum switching current | 5 MA for signalling circuit |
| Insulation resistance | > 10 MOhm for signalling circuit |
| Non-overlap time | 1.5 Ms on de-energisation between NC and NO contact<br>1.5 Ms on energisation between NC and NO contact |
| Mounting support | Rail<br>Plate |

## Environment

| | |
|---|---|
| Standards | IEC 60947-1<br>IEC 60947-4-1<br>GB/T 14048.4 |
| Product certifications | CE[RETURN]UKCA[RETURN]CCC |
| IP degree of protection | IP2X front face for main circuit conforming to IEC 60529<br>IP2X front face for coil circuit conforming to IEC 60529 |
| Protective treatment | TH conforming to IEC 60068-2-30 |
| Permissible ambient air temperature around the device | -40…60 °C operation<br>60…70 °C with derating<br>-60…80 °C storage |
| Operating altitude | 3000 m without derating |
| Fire resistance | 850 °C conforming to IEC 60695-2-11 |
| Mechanical robustness | Vibrations contactor open (2 Gn, 5...300 Hz) conforming to IEC 60068-2-6<br>Vibrations contactor closed (4 Gn, 5...300 Hz) conforming to IEC 60068-2-6<br>Shocks 11 ms contactor closed (15 gn) conforming to IEC 60068-2-27<br>Shocks 11 ms contactor open (8 gn) conforming to IEC 60068-2-27 |
| Height | 91 Mm |
| Width | 45 Mm |

| | |
|---|---|
| Depth | 99 Mm |
| Net weight | 0.425 Kg |

## Packing Units

| | |
|---|---|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 9.3 Cm |
| Package 1 Width | 11.6 Cm |
| Package 1 Length | 5.2 Cm |
| Package 1 Weight | 446.63 G |

## Offer Sustainability

| | |
|---|---|
| Recyclability potential, in % | 65 |
| Total lifecycle Carbon footprint | 329 kg CO2 eq. |
| Carbon footprint of the manufacturing phase [A1 to A3] | 2.367536798849649 |
| Carbon footprint of the manufacturing phase [A1 to A3] | 2 kg CO2 eq. |
| Carbon footprint of the distribution phase [A4] | 0.6539366820065979 |
| Carbon footprint of the distribution phase [A4] | 0.7 kg CO2 eq. |
| Carbon footprint of the installation phase [A5] | 0.001297330462801522 |
| Carbon footprint of the installation phase [A5] | 0 kg CO2 eq. |
| Carbon footprint of the use phase [B2, B3, B4, B6] | 325.6601958696018 |
| REACh free of SVHC | Yes |
| Carbon footprint of the use phase [B2, B3, B4, B6] | 326 kg CO2 eq. |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| Sustainable packaging | Yes |
| Carbon footprint of the end-of-life phase [C1 to C4] | 0.690435558850847 |
| Carbon footprint of the end-of-life phase [C1 to C4] | 0.7 kg CO2 eq. |
| Environmental Disclosure | Product Environmental Profile |
| Total lifecycle Carbon footprint | 329 |
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | Yes |
| REACh Regulation | Free of Substances of Very High Concern above the threshold |
| EU RoHS Directive | Compliant |
| PVC free | Yes |
| Silicone-free | Yes |
| End of life manual availability | End Of Life Information |
| Take-back | No |

## Contractual warranty

| | |
|---|---|
| Warranty (in months) | 18 |

Product Life Status : End of commerc. - Block