Product data sheet
Characteristics

LC1G4004EHEN
High power contactor, TeSys Giga, 4 pole (4NO), AC-1 <=440V 550A, standard version, 48…130V wide band AC/DC coil



Main

Range	TeSys
Range of product	TeSys Giga
Product or component type	Contactor
Device short name	LC1G
Contactor application	Power switching
Utilisation category	AC-3 AC-3e AC-1 AC-5a AC-5b AC-6a AC-6b DC-1 DC-3 DC-5
Poles description	4P
[Ue] rated operational voltage	<= 1000 V AC 50/60 Hz <= 460 V DC
[Ie] rated operational current	400 A (at <60 °C) at <= 440 V AC-3 550 A (at <40 °C) at <= 1000 V AC-1
[Uc] control circuit voltage	48...130 V AC 50/60 Hz 48...130 V DC
Control circuit voltage limits	Operational: 0.8 Uc Min...1.1 Uc Max (at <60 °C) Drop-out: 0.1 Uc Max...0.45 Uc Min (at <60 °C)

Complementary

[Uimp] rated impulse withstand voltage	8 KV
Overvoltage category	III
[Ith] conventional free air thermal current	550 A (at 40 °C)
Rated breaking capacity	3480 A at 440 V
[Icw] rated short-time withstand current	3.6 KA - 10 s 2.4 KA - 30 s 1.7 KA - 1 min 1.2 KA - 3 min 1.0 KA - 10 min
Associated fuse rating	500 A aM at <= 440 V for motor 315 A aM at <= 690 V for motor 630 A gG at <= 690 V 600 A UL Type L at <= 600 V
Average impedance	0.0001 Ohm
[Ui] rated insulation voltage	1000 V

Power dissipation per pole	30 W AC-1 - Ith 550 A 16 W AC-3 - Ith 400 A
Compatibility code	LC1G
Pole contact composition	4 NO
Auxiliary contact composition	1 NO + 1 NC
Irms rated making capacity	5090 A at 440 V
Coil technology	Built-in bidirectional peak limiting
Safety reliability level	B10d = 400000 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 3000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1
Mechanical durability	8 Mcycles
Inrush power in VA	965 VA
Inrush power in W	760 W
Hold-in power consumption in VA	17.6 VA
Hold-in power consumption in W	7.8 W
Operating time	40...70 ms closing 15...50 ms opening
Maximum operating rate	600 Cyc/H AC-3 600 Cyc/H AC-3e 300 Cyc/H AC-1
Connections - terminals	Power circuit: bar 2 - busbar cross section: 32 x 10 mm Power circuit: lugs-ring terminals 1 185 mm² Control circuit: push-in 1 0.2…2.5 mm² - cable stiffness: solid stranded without cable end Control circuit: push-in 1 0.25…2.5 mm² - cable stiffness: flexible with cable end Control circuit: push-in 2 0.5…1.0 mm² with cable end Control circuit: push-in 0.75…2.5 mm² - cable stiffness: solid stranded without cable end Control circuit: push-in 0.75…2.5 mm² - cable stiffness: flexible with cable end
Connection pitch	45 Mm
Mounting support	Plate
Standards	EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 CSA C22.2 No 60947-4-1 JIS C8201-4-1 JIS C8201-5-1 UL 60335-1 UL 60335-2-40:Annex JJ
Product certifications	CB Scheme[RETURN]CCC[RETURN]cULus[RETURN]EAC[RETURN]CE[RETURN]UKCA[RETUI
Tightening torque	35 N.M
Height	225 Mm
Width	185 Mm
Depth	226 Mm
Net weight	8.3 Kg

Environment

IP degree of protection	IP2X front face with shrouds conforming to IEC 60529 IP2X front face with shrouds conforming to VDE 0106
Ambient air temperature for operation	-25…60 °C
Ambient air temperature for storage	-60…80 °C
Mechanical robustness	Vibrations 5…300 Hz 2 gn contactor open Vibrations 5…300 Hz 4 gn contactor closed Shocks 10 gn 11 ms contactor open Shocks 15 gn 11 ms contactor closed
Colour	Dark grey
Protective treatment	TH
Permissible ambient air temperature around the device	-40…70 °C at Uc

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	27 Cm
Package 1 Width	31 Cm
Package 1 Length	31 Cm

Package 1 Weight	9.386 Kg
Unit Type of Package 2	P06
Number of Units in Package 2	8
Package 2 Height	75 Cm
Package 2 Width	60 Cm
Package 2 Length	80 Cm
Package 2 Weight	83.588 Kg

Offer Sustainability

Recyclability potential, in %	55
Total lifecycle Carbon footprint	2 712 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	79.22303366187975
Carbon footprint of the manufacturing phase [A1 to A3]	79 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	14.358916060924981
Carbon footprint of the distribution phase [A4]	14 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.11891397981313281
Carbon footprint of the installation phase [A5]	0.1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	2605.2815669568154
Carbon footprint of the use phase [B2, B3, B4, B6]	2 605 kg CO2 eq.
Mercury free	Yes
Sustainable packaging	Yes
Carbon footprint of the end-of-life phase [C1 to C4]	12.613764140010883
Carbon footprint of the end-of-life phase [C1 to C4]	13 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	2712
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	6fbdad13-bb7c-47d4-a6d6-d82dd6f54349
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Styrene, which is known to the
Halogen-free status	Halogen free plastic parts product
PVC free	Yes
End of life manual availability	End Of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection a

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised