Product data sheet
Characteristics

LC1G6304KUEN
High power contactor,TeSys Giga 630,4P(4NO),AC-1 <=440V 1050A,standard version,100-250V AC/DC wide band coil



Main

Range	TeSys
Range of product	TeSys Giga
Product or component type	Contactor
Device short name	LC1G
Contactor application	Power switching
Utilisation category	AC-3 AC-3e AC-1 AC-5a AC-5b AC-6a AC-6b DC-1 DC-3 DC-5
Poles description	4P
[Ue] rated operational voltage	<= 1000 V AC 50/60 Hz <= 460 V DC
[Ie] rated operational current	630 A (at <60 °C) at <= 440 V AC-3 1050 A (at <40 °C) at <= 1000 V AC-1
[Uc] control circuit voltage	100...250 V AC 50/60 Hz 100...250 V DC
Control circuit voltage limits	Operational: 0.8 Uc Min...1.1 Uc Max (at <60 °C) Drop-out: 0.1 Uc Max...0.45 Uc Min (at <60 °C)

Complementary

[Uimp] rated impulse withstand voltage	8 KV
Overvoltage category	III
[Ith] conventional free air thermal current	1050 A (at 40 °C)
Rated breaking capacity	5550 A at 440 V
[Icw] rated short-time withstand current	5.05 KA - 10 s 4.4 KA - 30 s 3.4 KA - 1 min 2.2 KA - 3 min 1.6 KA - 10 min
Associated fuse rating	630 A aM at <= 440 V for motor 500 A aM at <= 690 V for motor 1250 A gG at <= 690 V 1000 A UL Type L at <= 600 V
Average impedance	0.000065 Ohm
[Ui] rated insulation voltage	1000 V

Power dissipation per pole	70 W AC-1 - Ith 1050 A 26 W AC-3 - Ith 630 A
Compatibility code	LC1G
Pole contact composition	4 NO
Auxiliary contact composition	1 NO + 1 NC
Irms rated making capacity	7220 A at 440 V
Coil technology	Built-in bidirectional peak limiting
Safety reliability level	B10d = 100000 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 1800000 cycles contactor with mechanical load conforming to EN/ISO 13849-1
Mechanical durability	5 Mcycles
Inrush power in VA	800 VA
Inrush power in W	680 W
Hold-in power consumption in VA	15.0 VA
Hold-in power consumption in W	9.5 W
Operating time	40...70 ms closing 15...50 ms opening
Maximum operating rate	600 Cyc/H AC-3 600 Cyc/H AC-3e 300 Cyc/H AC-1
Connections - terminals	Power circuit: bar 2 - busbar cross section: 52 x 20 mm Power circuit: lugs-ring terminals 1 185 mm² Control circuit: push-in 1 0.2…2.5 mm² - cable stiffness: solid stranded without cable end Control circuit: push-in 1 0.25…2.5 mm² - cable stiffness: flexible with cable end Control circuit: push-in 2 0.5…1.0 mm² with cable end Control circuit: push-in 0.75…2.5 mm² - cable stiffness: solid stranded without cable end Control circuit: push-in 0.75…2.5 mm² - cable stiffness: flexible with cable end
Connection pitch	70 Mm
Mounting support	Plate
Standards	EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 CSA C22.2 No 60947-4-1 JIS C8201-4-1 JIS C8201-5-1 UL 60335-1 UL 60335-2-40:Annex JJ
Product certifications	CB Scheme[RETURN]CCC[RETURN]cULus[RETURN]EAC[RETURN]CE[RETURN]UKCA[RETUI
Tightening torque	58 N.M
Height	284 Mm
Width	281 Mm
Depth	266 Mm
Net weight	18 Kg

Environment

IP degree of protection	IP2X front face with shrouds conforming to IEC 60529 IP2X front face with shrouds conforming to VDE 0106
Ambient air temperature for operation	-25…60 °C
Ambient air temperature for storage	-60…80 °C
Mechanical robustness	Vibrations 5…300 Hz 2 gn contactor open Vibrations 5…300 Hz 4 gn contactor closed Shocks 10 gn 11 ms contactor open Shocks 15 gn 11 ms contactor closed
Colour	Dark grey
Protective treatment	TH
Permissible ambient air temperature around the device	-40…70 °C at Uc

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	34.000 Cm
Package 1 Width	37.000 Cm
Package 1 Length	51.000 Cm

Package 1 Weight	20.521 Kg
Unit Type of Package 2	P06
Number of Units in Package 2	2
Package 2 Height	75.000 Cm
Package 2 Width	60.000 Cm
Package 2 Length	80.000 Cm
Package 2 Weight	51.042 Kg

Offer Sustainability

Recyclability potential, in %	55
Total lifecycle Carbon footprint	5 723 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	165.96767124836578
Carbon footprint of the manufacturing phase [A1 to A3]	166 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	30.081098263082236
Carbon footprint of the distribution phase [A4]	30 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.24911790670239464
Carbon footprint of the installation phase [A5]	0.2 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	5500.038863575499
Carbon footprint of the use phase [B2, B3, B4, B6]	5 500 kg CO2 eq.
Mercury free	Yes
Sustainable packaging	No
Carbon footprint of the end-of-life phase [C1 to C4]	26.42510597269747
Carbon footprint of the end-of-life phase [C1 to C4]	26 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	5723
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	6fbdad13-bb7c-47d4-a6d6-d82dd6f54349
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Styrene and Bisphenol A (BPA
Halogen-free status	Halogen free plastic parts product
PVC free	Yes
End of life manual availability	End Of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection a

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised