Product data sheet
Characteristics

LG1K065Q707
Enclosed DOL starter,TeSys LG,1.6-2.5A,380/400V AC coil,including 1 LC1K,GV2ME,rotary isolation switch ,2 pushbuttons



Main

Range	TeSys
Product name	TeSys LG
Device short name	LG1K
Product or component type	Enclosed DOL starter
Device application	Safety
Utilisation category	AC-3
Device composition	Contactor Switch disconnector Circuit-breaker
Motor power kW	0.37 KW at 220/230 V AC 50/60 Hz 0.75 KW at 400/415 V AC 50/60 Hz 1.1 KW at 440 V AC 50/60 Hz
Thermal protection adjustment range	1.6…2.5 A
[Uc] control circuit voltage	380/400 V AC 50/60 Hz
Control type	Push-button start white I Push-button stop black O Rotary handle emergency stop red

Complementary

Cable entry number	4 2 Pg 13 + 2 Pg 16 top 4 2 Pg 13 + 2 Pg 16 bottom
Width	175 Mm
Height	165 Mm
Depth	165 Mm
Net weight	0.97 Kg

Environment

Standards	IEC 60947-4-1 IEC 60204-1
Product certifications	CE[RETURN]UKCA
Material	Polycarbonate
IK degree of protection	IK07 conforming to IEC 60529
IP degree of protection	IP55 conforming to IEC 60529
Environmental characteristic	Standard environment

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	22.500 Cm
Package 1 Width	24.000 Cm
Package 1 Length	27.000 Cm
Package 1 Weight	1.717 Kg
Unit Type of Package 2	P06
Number of Units in Package 2	12
Package 2 Height	75.000 Cm
Package 2 Width	60.000 Cm
Package 2 Length	80.000 Cm
Package 2 Weight	33.736 Kg

Offer Sustainability

Recyclability potential, in %	37
Total lifecycle Carbon footprint	124 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	8.743281674764857
Carbon footprint of the manufacturing phase [A1 to A3]	9 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.11740420167343783
Carbon footprint of the distribution phase [A4]	0.1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.00438148617842906
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	113.09865598349461
Carbon footprint of the use phase [B2, B3, B4, B6]	113 kg CO2 eq.
Mercury free	Yes
Sustainable packaging	Yes
Carbon footprint of the end-of-life phase [C1 to C4]	2.285960066539902
Carbon footprint of the end-of-life phase [C1 to C4]	2 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	124
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	7e14df67-eba2-4420-9585-9bffc1c2bbc8
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead, which is known to the State
End of life manual availability	End Of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised