# Product data sheet
## Characteristics

# LP4K0901BW3
Contactor, TeSys K, 3P, AC-3/AC-3e, 440V, 9A, 1NC aux, 24V DC low consumption coil




## Main

| | |
|---|---|
| Range | TeSys |
| Product or component type | Contactor |
| Device short name | LP4K |
| Contactor application | Motor control<br>Resistive load |

## Complementary

| | |
|---|---|
| Utilisation category | AC-3<br>AC-3e<br>AC-1<br>AC-4 |
| Poles description | 3P |
| Pole contact composition | 3 NO |
| [Ue] rated operational voltage | Power circuit: <= 690 V AC <= 400 Hz<br>Signalling circuit: <= 690 V AC <= 400 Hz |
| [Ie] rated operational current | 9 A (at <60 °C) at <= 440 V AC AC-3 for power circuit<br>9 A (at <60 °C) at <= 440 V AC AC-3e for power circuit<br>20 A (at <60 °C) at <= 690 V AC AC-1 for power circuit |
| Control circuit type | DC wide range |
| [Uc] control circuit voltage | 24 V DC |
| Motor power kW | 2.2 KW at 220...230 V AC 50/60 Hz AC-3<br>4 KW at 380...415 V AC 50/60 Hz AC-3<br>4 KW at 440/690 V AC 50/60 Hz AC-3<br>2.2 KW at 220...230 V AC 50/60 Hz AC-3e<br>4 KW at 380...415 V AC 50/60 Hz AC-3e<br>4 KW at 440/690 V AC 50/60 Hz AC-3e<br>2.2 KW at 220...230 V AC 50/60 Hz AC-4<br>4 KW at 380...415 V AC 50/60 Hz AC-4<br>4 KW at 440/690 V AC 50/60 Hz AC-4 |
| Auxiliary contact composition | 1 NC |
| [Uimp] rated impulse withstand voltage | 8 KV |
| Overvoltage category | III |
| [Ith] conventional free air thermal current | 20 A (at 60 °C) for power circuit<br>10 A (at 50 °C) for signalling circuit |
| Irms rated making capacity | 110 A AC for power circuit conforming to IEC 60947<br>110 A AC for signalling circuit conforming to IEC 60947 |
| Rated breaking capacity | 110 A at 220...230 V conforming to IEC 60947<br>110 A at 380...400 V conforming to IEC 60947<br>110 A at 415 V conforming to IEC 60947<br>110 A at 440 V conforming to IEC 60947<br>80 A at 500 V conforming to IEC 60947<br>70 A at 660...690 V conforming to IEC 60947 |

| | |
|---|---|
| [Icw] rated short-time withstand current | 90 A 50 °C - 1 s for power circuit<br>85 A 50 °C - 5 s for power circuit<br>80 A 50 °C - 10 s for power circuit<br>60 A 50 °C - 30 s for power circuit<br>45 A 50 °C - 1 min for power circuit<br>40 A 50 °C - 3 min for power circuit<br>20 A 50 °C - >= 15 min for power circuit<br>80 A - 1 s for signalling circuit<br>90 A - 500 ms for signalling circuit<br>110 A - 100 ms for signalling circuit |
| Associated fuse rating | 25 A gG at <= 440 V for power circuit<br>25 A aM for power circuit<br>10 A gG for signalling circuit conforming to IEC 60947<br>10 A gG for signalling circuit conforming to VDE 0660 |
| Average impedance | 3 MOhm - Ith 20 A 50 Hz for power circuit |
| [Ui] rated insulation voltage | Power circuit: 600 V conforming to UL 508<br>Power circuit: 690 V conforming to IEC 60947-4-1<br>Signalling circuit: 690 V conforming to IEC 60947-4-1<br>Signalling circuit: 690 V conforming to IEC 60947-5-1<br>Signalling circuit: 600 V conforming to UL 508<br>Power circuit: 600 V conforming to CSA C22.2 No 14<br>Signalling circuit: 600 V conforming to CSA C22.2 No 14 |
| Insulation resistance | > 10 MOhm for signalling circuit |
| Inrush power in W | 1.8 W (at 20 °C) |
| Hold-in power consumption in W | 1.8 W at 20 °C |
| Heat dissipation | 1.8 W |
| Control circuit voltage limits | Operational: 0.7...1.3 Uc (at <50 °C)<br>Drop-out: >= 0.10 Uc (at <50 °C) |
| Connections - terminals | Screw clamp terminals 1 cable(s) 1.5…4 mm²solid<br>Screw clamp terminals 1 cable(s) 0.75…4 mm²flexible without cable end<br>Screw clamp terminals 1 cable(s) 0.34…2.5 mm²flexible with cable end<br>Screw clamp terminals 2 cable(s) 1.5…4 mm²solid<br>Screw clamp terminals 2 cable(s) 0.75…4 mm²flexible without cable end<br>Screw clamp terminals 2 cable(s) 0.34…1.5 mm²flexible with cable end<br>Power circuit: screw clamp terminals 2 cable(s) 1.5 mm²flexible with cable end |
| Maximum operating rate | 3600 Cyc/H |
| Coil technology | With integral suppression device |
| Auxiliary contacts type | Type instantaneous 1 NC |
| Minimum switching current | 5 MA for signalling circuit |
| Minimum switching voltage | 17 V for signalling circuit |
| Mounting support | Rail<br>Plate |
| Tightening torque | 0.8…1.3 N.M - on screw clamp terminals Philips No 2<br>0.8…1.3 N.M - on screw clamp terminals flat Ø 6 mm<br>0.8…1.3 N.M - on screw clamp terminals pozidriv No 2 |
| Operating time | 10...20 ms coil de-energisation and NO opening<br>30...40 ms coil energisation and NO closing |
| Safety reliability level | B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1<br>B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1 |
| Mechanical durability | 30 Mcycles |
| Electrical durability | 1.3 Mcycles 9 A AC-3 at Ue <= 440 V<br>1.3 Mcycles 9 A AC-3e at Ue <= 440 V<br>0.16 Mcycles 20 A AC-1 at Ue <= 690 V<br>0.02 Mcycles 54 A AC-4 at Ue <= 440 V |
| Height | 58 Mm |
| Width | 45 Mm |
| Depth | 57 Mm |
| Net weight | 0.235 Kg |

## Environment

| | |
|---|---|
| Standards | EN/IEC 60947-4-1<br>EN/IEC 60947-5-1<br>UL 60947-4-1<br>UL 60947-5-1<br>CSA C22.2 No 60947-4-1<br>CSA C22.2 No 60947-5-1<br>GB/T 14048.4 |
| Product certifications | CB Scheme[RETURN]CCC[RETURN]UL[RETURN]CSA[RETURN]EAC[RETURN]CE[RETURN |
| IP degree of protection | IP2X |
| Ambient air temperature for operation | -25…50 °C |
| Ambient air temperature for storage | -50…80 °C |
| Operating altitude | 2000 m without derating |
| Flame retardance | V1 conforming to UL 94<br>Requirement 2 conforming to NF F 16-101<br>Requirement 2 conforming to NF F 16-102 |

## Packing Units

| | |
|---|---|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 6.600 Cm |
| Package 1 Width | 4.800 Cm |
| Package 1 Length | 6.200 Cm |
| Package 1 Weight | 221.000 G |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 40 |
| Package 2 Height | 15.000 Cm |
| Package 2 Width | 30.000 Cm |
| Package 2 Length | 40.000 Cm |
| Package 2 Weight | 9.222 Kg |
| Unit Type of Package 3 | P06 |
| Number of Units in Package 3 | 320 |
| Package 3 Height | 45.000 Cm |
| Package 3 Width | 60.000 Cm |
| Package 3 Length | 80.000 Cm |
| Package 3 Weight | 82.540 Kg |

## Offer Sustainability

| | |
|---|---|
| Recyclability potential, in % | 63 |
| Total lifecycle Carbon footprint | 119 kg CO2 eq. |
| Carbon footprint of the manufacturing phase [A1 to A3] | 1.1348165272383228 |
| Carbon footprint of the manufacturing phase [A1 to A3] | 1 kg CO2 eq. |
| Carbon footprint of the distribution phase [A4] | 0.4379807907104773 |
| Carbon footprint of the distribution phase [A4] | 0.4 kg CO2 eq. |
| Carbon footprint of the installation phase [A5] | 0.030109360466276436 |
| Carbon footprint of the installation phase [A5] | 0 kg CO2 eq. |
| Carbon footprint of the use phase [B2, B3, B4, B6] | 116.84560644093847 |
| REACh free of SVHC | Yes |
| Carbon footprint of the use phase [B2, B3, B4, B6] | 117 kg CO2 eq. |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| Sustainable packaging | Yes |
| Carbon footprint of the end-of-life phase [C1 to C4] | 0.3180571443438615 |
| Carbon footprint of the end-of-life phase [C1 to C4] | 0.3 kg CO2 eq. |
| Environmental Disclosure | Product Environmental Profile |
| Total lifecycle Carbon footprint | 119 |

| | |
|---|---|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | Yes |
| REACh Regulation | Reference contains Substances of Very High Concern above the threshold |
| EU RoHS Directive | Compliant |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Antimony oxide &amp Antimony t |
| POP Directive | No POPs |
| End of life manual availability | End Of Life Information |
| Take-back | No |
| WEEE Label | The product must be disposed on European Union markets following specific waste collection and |

## Contractual warranty

| | |
|---|---|
| Warranty (in months) | 18 |

Product Life Status : Commercialised