Product data sheet
Characteristics

LR97D07M7
Electronic overcurrent relay, TeSys LR97D, 200 to 240VAC, 1.2 to 7A, 1C/O



Main

Range	TeSys
Product name	TeSys D
Device short name	LR97
Product or component type	Electronic overcurrent relay
Relay application	Sensitivity to phase failure Locked rotor, mechanical jamming I > 3 x Isetting Overload Imax > Isetting
Product compatibility	LC1D09...D38
Network type	AC
[Us] rated supply voltage	200...240 V AC
Thermal protection adjustment range	1.2…7 A
[Ue] rated operational voltage	600 V AC 50/60 Hz for power circuit conforming to CSA 600 V AC 50/60 Hz for power circuit conforming to UL 690 V AC 50/60 Hz for power circuit conforming to IEC 60947-4-1
Quantity per set	Set of 10

Complementary

Network frequency	50...60 Hz
Mounting support	Direct on contactor Rail
Tripping threshold	1.2...6 A
Surge withstand	6 KV conforming to IEC 61000-4-5
Contacts type and composition	1 C/O
[Ith] conventional free air thermal current	3 A for control circuit
Protection type	BS fuse 3 A - for control circuit GB2 circuit breaker 3 A - for control circuit GG fuse 3 A - for control circuit
Maximum power	28 W at 110 V DC conforming to IEC 60947 28 W at 220 V DC conforming to IEC 60947 55 W at 24 V DC conforming to IEC 60947 55 W at 48 V DC conforming to IEC 60947 140 VA at 48 V AC conforming to IEC 60947 360 VA at 110 V AC conforming to IEC 60947 360 VA at 220 V AC conforming to IEC 60947 70 VA at 24 V AC conforming to IEC 60947
[Ui] rated insulation voltage	Power circuit: 600 V conforming to CSA Power circuit: 600 V conforming to UL Power circuit: 690 V conforming to IEC 60947-4-1
[Uimp] rated impulse withstand voltage	6 KV
Phase failure sensitivity	< 3 s

Reset	Automatic reset 120 s fixed Electrical by interruption of power supply for minimum 0.1 s Manual reset
Time range	0.2...10 s - O-time knob 0.3...10 s - O-time knob 0.5..30 s - D-time knob
Signalling function	2 LEDs
Connections - terminals	Control circuit: cable 1 x 1…25 mm²flexible with cable end Control circuit: cable 1 x 1…25 mm²flexible without cable end Power circuit: cable 1 x 1…4 mm²flexible with cable end Power circuit: cable 1 x 1.5…10 mm²flexible without cable end Power circuit: lug-clamp 1 x 1…4 mm²flexible with cable end Power circuit: lug-clamp 1 x 1.5…10 mm²flexible without cable end Control circuit: cable 2 x 1…25 mm²flexible with cable end Control circuit: cable 2 x 1…25 mm²flexible without cable end Control circuit: lug-clamp 1 x 1…25 mm²flexible with cable end Control circuit: lug-clamp 1 x 1…25 mm²flexible without cable end Control circuit: lug-clamp 2 x 1…25 mm²flexible with cable end Control circuit: lug-clamp 2 x 1…25 mm²flexible without cable end
Tightening torque	Control circuit: 0.6...1.2 N.m on lug-clamp Power circuit: 2 N.m on cable
Height	67.5 Mm
Width	45 Mm
Depth	67.5 Mm
Net weight	0.172 Kg

Environment

Standards	IEC 60947 IEC 60255-6
Product certifications	GOST[RETURN]CSA[RETURN]UL
Protective treatment	TH conforming to IEC 60068
IP degree of protection	IP20 conforming to IEC 60529
Ambient air temperature for operation	-25…60 °C conforming to IEC 60947-4-1
Ambient air temperature for storage	-30…80 °C
Operating altitude	2000 m
Fire resistance	850 °C conforming to IEC 60695-2-1
Shock resistance	15 gn 11 ms conforming to IEC 60068-2-7
Vibration resistance	4 gn conforming to IEC 60068-2-6
Dielectric strength	2 V 50 Hz conforming to IEC 60255-5
Resistance to electrostatic discharge	6 KV in indirect mode 8 KV in air
Resistance to radiated fields	10 V/M level 3
Resistance to fast transients	2 KV
Disturbance radiated/conducted	10 V conforming to EN 61000-4-6 Class A conforming to EN 55011

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.33 Cm
Package 1 Width	7.11 Cm
Package 1 Length	7.62 Cm
Package 1 Weight	0.19 Kg
Unit Type of Package 2	S02
Number of Units in Package 2	24
Package 2 Height	15 Cm
Package 2 Width	30 Cm
Package 2 Length	40 Cm
Package 2 Weight	5.04 Kg
Unit Type of Package 3	PAL
Number of Units in Package 3	384

Package 3 Height	77 Cm
Package 3 Width	80 Cm
Package 3 Length	60 Cm
Package 3 Weight	86.052 Kg

Offer Sustainability

Recyclability potential, in %	31
Total lifecycle Carbon footprint	32 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	3.5984962575887334
Carbon footprint of the manufacturing phase [A1 to A3]	4 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.18771836256245691
Carbon footprint of the distribution phase [A4]	0.2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.0014389305343457974
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	27.717393653663148
Carbon footprint of the use phase [B2, B3, B4, B6]	28 kg CO2 eq.
Mercury free	Yes
Sustainable packaging	No
Carbon footprint of the end-of-life phase [C1 to C4]	0.2591871485505685
Carbon footprint of the end-of-life phase [C1 to C4]	0.3 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	32
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	99e36f9f-1e4f-4e3a-a849-bdda6ef53eb9
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony tr
End of life manual availability	End Of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection a

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised