Product data sheet
Characteristics

LUA1C20
Auxiliary contact, TeSys Ultra, 2NO, 690VAC/ DC, for for Fault signalling, Screw clamp terminals



Main

Range	TeSys
Device short name	LUA1
Product or component type	Auxiliary contact

Complementary

Auxiliary contact composition	2 NO
Signalling function	Fault signalling Indicating rotary knob in ready position
[Ue] rated operational voltage	<= 250 V AC <= 250 V DC
[Ui] rated insulation voltage	250 V conforming to CSA 250 V conforming to IEC 60947-5-1 250 V conforming to UL
[Ith] conventional free air thermal current	2.5 A
Minimum switching voltage	17 V
Minimum switching current	5 MA
Net weight	0.03 Kg
Connections - terminals	Screw clamp terminals

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.000 Cm
Package 1 Width	9.000 Cm
Package 1 Length	10.000 Cm
Package 1 Weight	25.000 G
Unit Type of Package 2	S01
Number of Units in Package 2	30
Package 2 Height	15.000 Cm
Package 2 Width	15.000 Cm
Package 2 Length	40.000 Cm
Package 2 Weight	931.000 G
Unit Type of Package 3	P06
Number of Units in Package 3	960
Package 3 Height	75.000 Cm
Package 3 Width	60.000 Cm

Package 3 Length	80.000 Cm
Package 3 Weight	37.792 Kg

Offer Sustainability

REACh free of SVHC	Yes
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	Yes
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised