Product data sheet
Characteristics

LUFDA01
Function module, TeSys Ultra, 1NC, 24 to 240VDC, Front side, thermal overload signalling



Main

Range	TeSys
Device short name	LUF
Product or component type	Function module
Product compatibility	LUCB...BL[RETURN]LUCC...ES[RETURN]LUCD...FU[RETURN]LUCD...BL[RETURN]LUCC...

Complementary

Mounting mode	Plug-in
Mounting location	Front side
Function available	Thermal overload signalling and automatic or remote reset
Auxiliary contact composition	1 NC
Communication of faults	LED front panel
[Us] rated supply voltage	24...240 V DC
[Ith] conventional free air thermal current	2 A 70 °C
Short-circuit protection	2 A fuse gG conforming to IEC 60947-5-1
Connection pitch	5.08 Mm
Tightening torque	0.5…0.6 N.M - with screwdriver 3.5 mm flat
Net weight	0.055 Kg

Environmental

Standards	UL 60947-4-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.300 Cm
Package 1 Width	4.700 Cm
Package 1 Length	10.500 Cm
Package 1 Weight	74.000 G
Unit Type of Package 2	S01
Number of Units in Package 2	20
Package 2 Height	15.000 Cm
Package 2 Width	15.000 Cm
Package 2 Length	40.000 Cm
Package 2 Weight	1.697 Kg

Offer Sustainability

Mercury free	Yes
Sustainable packaging	Yes
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	E383808a-7832-4e0a-8697-e499929809d4
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
Halogen-free status	Halogen free plastic parts product
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised