Product data sheet
Characteristics

LULC08
Communication module, TeSys Ultra, 24VDC, 0 to 500mA, CANopen, front side



Main

Range	TeSys
Device short name	LUL
Product or component type	Communication module
Product compatibility	LUCA LUCL LUCD LUCC LUCM LUCB
Device application	Communication
Range compatibility	TeSys TeSys U LUB non reversing power base TeSys TeSys U LU2B reversing power base

Complementary

Function available	Communication module
Mounting mode	Plug-in
Mounting location	Front side
Physical interface	9-way SUB-D female
Bus type	CANopen
Communication port protocol	CAN2.0A CAN2.B
Addressing	1...127
Current consumption	1.5 mA at 24 V DC 20...28 V
Logic input	Positive at 24 V DC - 7 mA
Response time	10 ms +/- 30 % change to state 0 10 ms +/- 30 % change to state 1
Input type	Resistive
Number of outputs	2 dedicated to starter-controller coil operation 1
[Us] rated supply voltage	24 V DC
Output current	<= 500 mA
Protection type	GL fuse 2 A
Switching current capacity	0.5 MA at 24 V
Local signalling	3 LEDs front panel
Connection pitch	3.81 Mm

Connections - terminals	Screw clamp terminals 1 cable(s) 0.14…1 mm²flexible without cable end Screw clamp terminals 1 cable(s) 0.14…1 mm²rigid without cable end Screw clamp terminals 1 cable(s) 0.25…0.5 mm²flexible with cable end Screw clamp terminals 1 cable(s) 0.25…1 mm²flexible with cable end Screw clamp terminals 2 cable(s) 0.14…0.5 mm²rigid without cable end Screw clamp terminals 2 cable(s) 0.14…0.75 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.25…0.34 mm²flexible with cable end Screw clamp terminals 2 cable(s) 0.5 mm²flexible with cable end
Associated cable type	AWG 26...AWG 16
Tightening torque	0.2…0.25 N.M2.5 Mm

Environment

Standards	DR 303-2 CIADS-301 V4.02
Ambient air temperature for operation	-25…55 °C
IP degree of protection	IP20 conforming to IEC 60529

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.900 Cm
Package 1 Width	4.900 Cm
Package 1 Length	11.300 Cm
Package 1 Weight	104.000 G
Unit Type of Package 2	S02
Number of Units in Package 2	35
Package 2 Height	15.000 Cm
Package 2 Width	30.000 Cm
Package 2 Length	40.000 Cm
Package 2 Weight	3.923 Kg

Offer Sustainability

Mercury free	Yes
Sustainable packaging	Yes
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	E383808a-7832-4e0a-8697-e499929809d4
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
Halogen-free status	Halogen free plastic parts product
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised