
Product data sheet
Characteristics

LV846321
Switch disconnector, MasterPact MTZ2 25HH, 2500A, 220kA/440VAC 50/60Hz (Icm), 4P, drawout



Main

Range	MasterPact
Product or component type	Switch disconnector
Device application	Distribution
Switch-disconnector name	MasterPact MTZ2 25 HH
Poles description	4P
Neutral position	Left
Network type	AC
Network frequency	50/60 Hz

Complementary

Control type	Push-button
Mounting mode	Drawout
Mounting support	Chassis
[Ue] rated operational voltage	440 V AC 50/60 Hz conforming to EN/IEC 60947-3
[Ie] rated operational current	2500 A AC 50/60 Hz 440 V
[Ui] rated insulation voltage	1000 V AC 50/60 Hz conforming to EN/IEC 60947-3
[Uimp] rated impulse withstand voltage	12 KV conforming to EN/IEC 60947-3
[Icw] rated short-time withstand current	75 KA during 3 s conforming to EN/IEC 60947-3 100 KA during 1 s conforming to EN/IEC 60947-3
[Icm] rated short-circuit making capacity	220 KA peak 220/415 V AC at 50/60 Hz 220 KA peak 440 V AC at 50/60 Hz
Utilisation category	AC-23A AC-3
Breaking capacity	100 KA Icu at 220/415 V AC 50/60 Hz conforming to EN/IEC 60947-2 100 KA Icu at 440 V AC 50/60 Hz conforming to EN/IEC 60947-2
[Ics] rated service breaking capacity	100 KA at 220/415 V AC 50/60 Hz conforming to EN/IEC 60947-2 100 KA at 440 V AC 50/60 Hz conforming to EN/IEC 60947-2
Breaking capacity code	HH
Suitability for isolation	Yes conforming to EN/IEC 60947-3
Contact position indicator	Yes
Visible break	No
Mechanical durability	15000 Cycles with periodic preventive maintenance conforming to EN/IEC 60947-3
Electrical durability	AC-23A: 5000 cycles 440 V AC 50/60 Hz conforming to EN/IEC 60947-3
Connection pitch	115 Mm
Height	439 Mm
Width	556 Mm
Depth	403 Mm

Environment

Net weight	120 Kg
Standards	EN/IEC 60947-3
Product certifications	IECEE CB Scheme
IP degree of protection	IP30
Pollution degree	3 conforming to EN/IEC 60947-4-1
Ambient air temperature for operation	-25…70 °C
Ambient air temperature for storage	-40…85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	43.9 Cm
Package 1 Width	55.6 Cm
Package 1 Length	40.3 Cm
Package 1 Weight	120.0 Kg

Offer Sustainability

Recyclability potential, in %	71
Total lifecycle Carbon footprint	4 198 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	660.2522926829268
Carbon footprint of the manufacturing phase [A1 to A3]	660 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	14.297619512195123
Carbon footprint of the distribution phase [A4]	14 kg CO2 eq.
Carbon footprint of the installation phase [A5]	16.582829268292684
Carbon footprint of the installation phase [A5]	17 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	3290.9986146341466
Carbon footprint of the use phase [B2, B3, B4, B6]	3 291 kg CO2 eq.
Mercury free	Yes
Sustainable packaging	No
Carbon footprint of the end-of-life phase [C1 to C4]	216.20370731707317
Carbon footprint of the end-of-life phase [C1 to C4]	216 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	4198
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No, we have minimized the use of plastic in the packaging in compliance with regulations and cons
SCIP Number	F31d8a4d-e9cb-4afc-bf2c-5965742ce772
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
Halogen-free status	Product contains halogen above thresholds
PVC free	Yes
Silicone-free	No
End of life manual availability	End Of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised