Product data sheet
Characteristics

LV847227
Circuit breaker frame, MasterPact MTZ1 10L1 drawout for MicroLogic X, 1000A, 150kA/415VAC (Icu), 4P



Main

Range	MasterPacT
Product name	MasterPact MTZ1
Device short name	MTZ1 10 L1
Product or component type	Circuit breaker
Device application	Power distribution protection
Poles description	4P
Neutral position	Left
Control type	Without control unit
Product compatibility	Control unit MicroLogic 2.0 X Control unit MicroLogic 5.0 X Control unit MicroLogic 6.0 X Control unit MicroLogic 7.0 X Control unit MicroLogic 2.0 Xi Control unit MicroLogic 5.0 Xi Control unit MicroLogic 6.0 Xi Control unit MicroLogic 7.0 Xi
[In] rated current	1000 A at 40 °C
Breaking capacity code	L1 150 kA 415 V AC
[Ue] rated operational voltage	690 V AC 50/60 Hz
Suitability for isolation	Yes conforming to EN/IEC 60947-2
Utilisation category	Category A
Control type	Push-button
Mounting mode	Drawout

Complementary

Breaking capacity	150 KA at 220/415 V AC 50/60 Hz 130 KA at 440 V AC 50/60 Hz 100 KA at 500/525 V AC 50/60 Hz
[Ics] rated service breaking capacity	150 KA at 220/415 V AC 50/60 Hz 130 KA at 440 V AC 50/60 Hz 100 KA at 500/525 V AC 50/60 Hz
[Icw] rated short-time withstand current	10 KA 0.5 s
[Icm] rated short-circuit making capacity	330 KA 220/415 V AC at 50/60 Hz 286 KA 440 V AC at 50/60 Hz 220 KA 500/525 V AC at 50/60 Hz 52 KA 660/690 V AC at 50/60 Hz
Integral instant protection	9…11 KA
Circuit breaker CT rating	400 A 630 A 800 A 1000 A

[Ui] rated insulation voltage	1000 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	12 KV
Power dissipation in W	230 W
Maximum breaking time	9 Ms
Maximum closing response time	50 Ms
Mounting support	Rails Base plate
Upside connection	Front Rear
Downside connection	Front Rear
Connection pitch	70 Mm
Mechanical durability	12500 Cycles with periodic preventive maintenance
Electrical durability	AC-23A: 3000 cycles 690 V AC 50/60 Hz conforming to EN/IEC 60947-3 AC-23A: 6000 cycles 440 V AC 50/60 Hz conforming to EN/IEC 60947-3 AC-3: 6000 cycles 440 V AC 50/60 Hz conforming to EN/IEC 60947-3 2000 Cycles 690 V AC 50/60 Hz conforming to EN/IEC 60947-2 3000 Cycles 440 V AC 50/60 Hz conforming to EN/IEC 60947-2
Height	Drawout circuit breaker with chassis: 322 mm Drawout circuit breaker without chassis: 259.5 mm
Width	Drawout circuit breaker with chassis: 358 mm Drawout circuit breaker without chassis: 306.5 mm
Depth	Drawout circuit breaker with chassis: 291 mm Drawout circuit breaker without chassis: 207.5 mm
Net weight	39 Kg
Standards	EN/IEC 60947-1 EN/IEC 60947-2 EN/IEC 60947-2 Annex H IEC 61557-12
Product certifications	CE[RETURN]IECEE CB Scheme

Environment

IP degree of protection	IP30 conforming to EN 60529
Pollution degree	3 conforming to IEC 60947-1
Ambient air temperature for operation	-25…70 °C
Ambient air temperature for storage	-40…85 °C
Operating altitude	0...2000 m without derating 2000...5000 m with derating

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	40.0 Cm
Package 1 Width	30.0 Cm
Package 1 Length	40.0 Cm
Package 1 Weight	24.118 Kg

Offer Sustainability

Recyclability potential, in %	73
Total lifecycle Carbon footprint	1 675 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	277.98581196581193
Carbon footprint of the manufacturing phase [A1 to A3]	278 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	6.694735042735043
Carbon footprint of the distribution phase [A4]	7 kg CO2 eq.
Carbon footprint of the installation phase [A5]	27.66545299145299
Carbon footprint of the installation phase [A5]	28 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	1283.9212307692308
Carbon footprint of the use phase [B2, B3, B4, B6]	1 284 kg CO2 eq.
Mercury free	Yes
Sustainable packaging	No

Carbon footprint of the end-of-life phase [C1 to C4]	78.46294017094017
Carbon footprint of the end-of-life phase [C1 to C4]	78 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	1675
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No, we have minimized the use of plastic in the packaging in compliance with regulations and c
SCIP Number	44ce05ea-25e9-435c-886d-b1162ae4666b
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, wh
Halogen-free status	Product contains halogen above thresholds
PVC free	No
End of life manual availability	End Of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection a

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised