Product data sheet
Characteristics

LV847253
Switch disconnector, MasterPact MTZ1 10HA, 1000A, 75kA/690VAC 50/60Hz (Icm), 4P, drawout



Main

Range	MasterPact
Product or component type	Switch disconnector
Device application	Distribution
Switch-disconnector name	MasterPact MTZ1 10 HA
Poles description	4P
Neutral position	Left
Network type	AC
Network frequency	50/60 Hz

Complementary

Control type	Push-button
Mounting mode	Drawout
Mounting support	Chassis
Upside connection	Front
Downside connection	Front
[Ue] rated operational voltage	690 V AC 50/60 Hz conforming to EN/IEC 60947-3
[Ie] rated operational current	1000 A AC 50/60 Hz 690 V
[Ui] rated insulation voltage	1000 V AC 50/60 Hz conforming to EN/IEC 60947-3
[Uimp] rated impulse withstand voltage	12 KV conforming to EN/IEC 60947-3
[Icw] rated short-time withstand current	20 KA during 3 s conforming to EN/IEC 60947-3 36 KA during 0.5 s conforming to EN/IEC 60947-3 36 KA during 1 s
[Icm] rated short-circuit making capacity	75 KA peak 220...690 V AC at 50/60 Hz
Utilisation category	AC-23A AC-3
Breaking capacity code	HA
Suitability for isolation	Yes conforming to EN/IEC 60947-3
Contact position indicator	Yes
Visible break	No
Mechanical durability	12500 Cycles with periodic preventive maintenance conforming to EN/IEC 60947-3
Electrical durability	AC-23A: 6000 cycles 440 V AC 50/60 Hz conforming to EN/IEC 60947-3 AC-23A: 3000 cycles 690 V AC 50/60 Hz conforming to EN/IEC 60947-3 AC-3: 6000 cycles 440 V AC 50/60 Hz conforming to EN/IEC 60947-3
Connection pitch	70 Mm
Height	322 Mm
Width	358 Mm
Depth	291 Mm

Environment

Net weight	39 Kg
Standards	EN/IEC 60947-3
Product certifications	IECEE CB Scheme
IP degree of protection	IP30
Pollution degree	3 conforming to EN/IEC 60947-4-1
Ambient air temperature for operation	-25…70 °C
Ambient air temperature for storage	-40…85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	41.0 Cm
Package 1 Width	39.0 Cm
Package 1 Length	30.0 Cm
Package 1 Weight	21.375 Kg

Offer Sustainability

Recyclability potential, in %	73
Total lifecycle Carbon footprint	1 244 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	277.98581196581193
Carbon footprint of the manufacturing phase [A1 to A3]	278 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	6.694735042735043
Carbon footprint of the distribution phase [A4]	7 kg CO2 eq.
Carbon footprint of the installation phase [A5]	27.66545299145299
Carbon footprint of the installation phase [A5]	28 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	853.0690568561874
Carbon footprint of the use phase [B2, B3, B4, B6]	853 kg CO2 eq.
Mercury free	Yes
Sustainable packaging	No
Carbon footprint of the end-of-life phase [C1 to C4]	78.46294017094017
Carbon footprint of the end-of-life phase [C1 to C4]	78 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	1244
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No, we have minimized the use of plastic in the packaging in compliance with regulations and cons
SCIP Number	44ce05ea-25e9-435c-886d-b1162ae4666b
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
Halogen-free status	Product contains halogen above thresholds
PVC free	No
Silicone-free	No
End of life manual availability	End Of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised