
Product data sheet
Characteristics

LV847906
Microswitches OF/SDE/PF/CH, MasterPact MTZ1, with wires



Main

Range	MasterPact
Device short name	OF[RETURN]PF[RETURN]micro switch[RETURN]SDE
Product or component type	Auxiliary contact block
Device application	Control
Range compatibility	MasterPact MTZ1 circuit breaker

Complementary

Auxiliary contacts type	Standard
Signal contacts composition	4 NO/NC
Breaking capacity	6 A AC-12 240/380 V AC 50/60 Hz 0.5 A DC-12 125 V DC 6 A AC-12 480 V AC 50/60 Hz 6 A AC-12 690 V AC 50/60 Hz 2.5 A DC-12 24/48 V DC 0.3 A DC-12 250 V DC
Minimum load	100 MA at 24 V

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.500 Cm
Package 1 Width	6.500 Cm
Package 1 Length	10.000 Cm
Package 1 Weight	18.000 G
Unit Type of Package 2	BB1
Number of Units in Package 2	20
Package 2 Height	9.000 Cm
Package 2 Width	19.500 Cm
Package 2 Length	29.800 Cm
Package 2 Weight	498.000 G
Unit Type of Package 3	S03
Number of Units in Package 3	80
Package 3 Height	30.000 Cm
Package 3 Width	30.000 Cm
Package 3 Length	40.000 Cm
Package 3 Weight	2.467 Kg

Offer Sustainability

REACh free of SVHC	Yes
Mercury free	Yes
Sustainable packaging	Yes
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the Stat
Halogen-free status	Product contains halogen above thresholds
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised