Product data sheet
Characteristics

LVS03002
Rail, PrismaSeT G, for adjustable modular device, W600mm



Main

Range	PrismaSeT
Range of product	PrismaSeT G
Product or component type	Rail
Accessory / separate part category	Installation accessory
Range compatibility	PrismaSeT PrismaSeT G
Type of rail	Modular Adjustable
Installed device	TeSys: fixed GV2L TeSys: fixed GV2P TeSys: fixed GV3 ComPact: fixed NG160 without earth leakage protection - control: toggle ComPact: fixed NG160 NA without earth leakage protection - control: toggle ComPact: fixed NG160 with earth leakage protection - control: toggle ComPact: fixed NSXm without earth leakage protection - control: toggle - vertical installation ComPact: fixed NSXm with earth leakage protection - control: toggle - vertical installation
Poles description	9 x 3P: fixed GV2L 9 x 3P: fixed GV2P 7 x 3P: fixed GV3 1 x 3P: fixed NG160 1 x 4P: fixed NG160 1 x 3P: fixed NG160 NA 1 x 4P: fixed NG160 NA 1 x 3P or 4P: fixed NSXm vertical installation

Complementary

Enclosure/cubicle description	Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm
Number of vertical modules [50 mm]	3 module(s): GV2L, direct in 600 mm Widefloor-standing enclosure 3 module(s): GV2L, direct in 600 mm Widewall-mounted enclosure 3 module(s): GV2P, direct in 600 mm Widefloor-standing enclosure 3 module(s): GV2P, direct in 600 mm Widewall-mounted enclosure 5 module(s): GV3, direct in 600 mm Widefloor-standing enclosure 5 module(s): GV3, direct in 600 mm Widewall-mounted enclosure 5 module(s): NG160 without earth leakage protection , direct in 600 mm Widefloor-standing enclos 5 module(s): NG160 without earth leakage protection , direct in 600 mm Widewall-mounted enclos 5 module(s): NG160 NA without earth leakage protection , direct in 600 mm Widefloor-standing en 5 module(s): NG160 NA without earth leakage protection , direct in 600 mm Widewall-mounted en 7 module(s): NSXm without earth leakage protection , direct in 600 mm Widefloor-standing enclos 7 module(s): NSXm without earth leakage protection , direct in 600 mm Widewall-mounted enclos 7 module(s): NSXm without earth leakage protection , connection block in 600 mm Widefloor-stan 7 module(s): NSXm without earth leakage protection , connection block in 600 mm Widewall-mou 5 module(s): NG160 with earth leakage protection , direct in 600 mm Widefloor-standing enclosur 5 module(s): NG160 with earth leakage protection , direct in 600 mm Widewall-mounted enclosure 7 module(s): NSXm with earth leakage protection , direct in 600 mm Widefloor-standing enclosure 7 module(s): NSXm with earth leakage protection , direct in 600 mm Widewall-mounted enclosure 7 module(s): NSXm with earth leakage protection , connection block in 600 mm Widefloor-standin 7 module(s): NSXm with earth leakage protection , connection block in 600 mm Widewall-mounte
9 mm pitches	48
Quantity per set	Set of 1
Height	58 Mm
Width	467 Mm
Depth	97 Mm
Net weight	0.34 Kg
Colour	Natural
Material	Metal

Environment

Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASTA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.500 Cm
Package 1 Width	5.700 Cm
Package 1 Length	46.800 Cm
Package 1 Weight	311.000 G
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	15.500 Cm
Package 2 Width	31.000 Cm
Package 2 Length	49.000 Cm
Package 2 Weight	3.540 Kg
Unit Type of Package 3	P12
Number of Units in Package 3	300
Package 3 Height	104.000 Cm
Package 3 Width	80.000 Cm
Package 3 Length	120.000 Cm
Package 3 Weight	107.300 Kg

Offer Sustainability

REACh free of SVHC	Yes
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	Yes
Environmental Disclosure	Product Environmental Profile
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
Halogen-free status	Halogen free plastic parts product
PVC free	Yes
Silicone-free	Yes
End of life manual availability	No need of specific recycling operations
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised