Product data sheet
Characteristics

LVS03006
Rail, PrismaSeT G, for modular device, W850mm



Main

Range	PrismaSeT
Range of product	PrismaSeT G
Product or component type	Rail
Accessory / separate part category	Installation accessory
Range compatibility	PrismaSeT PrismaSeT G
Type of rail	Modular
Installed device	Acti 9: fixed iC120 without earth leakage protection - control: toggle ComPact: fixed INS100 - control: direct front rotary handle - vertical installation ComPact: fixed INS160 - control: direct front rotary handle - vertical installation ComPact: fixed INS40 - control: direct front rotary handle - vertical installation ComPact: fixed INS63 - control: direct front rotary handle - vertical installation Acti 9: fixed modular device Multi9: fixed modular device Multi9: fixed NG125 without earth leakage protection - control: toggle Acti 9: fixed iC120 with earth leakage protection - control: toggle ComPact: fixed INS125 - control: direct front rotary handle - vertical installation Acti 9: fixed modular device <= 40 A Multi9: fixed modular device <= 40 A Multi9: fixed NG125 with earth leakage protection
Poles description	24 x 1P: fixed iC120 12 x 2P: fixed iC120 8 x 3P: fixed iC120 6 x 4P: fixed iC120 4 x 3P: fixed INS100 vertical installation 4 x 4P: fixed INS100 vertical installation 4 x 3P: fixed INS125 vertical installation 4 x 4P: fixed INS125 vertical installation 4 x 3P: fixed INS160 vertical installation 4 x 4P: fixed INS160 vertical installation 4 x 3P: fixed INS40 vertical installation 4 x 4P: fixed INS40 vertical installation 4 x 3P: fixed INS63 vertical installation 4 x 4P: fixed INS63 vertical installation 12 x 2P: fixed NG125 8 x 3P: fixed NG125 6 x 4P: fixed NG125 5 x 2P: fixed iC120 3 x 3P: fixed iC120 3 x 4P: fixed iC120 6 x 2P: fixed NG125 4 x 3P: fixed NG125 3 x 4P: fixed NG125

Complementary

Enclosure/cubicle description	Floor-standing enclosure - width 850 mm
Number of vertical modules [50 mm]	5 module(s): iC120 without earth leakage protection , direct in 850 mm Widefloor-standing enclosu 4 module(s): INS100, direct in 850 mm Widefloor-standing enclosure 5 module(s): INS100, direct in 850 mm Widefloor-standing enclosure 4 module(s): INS125, direct in 850 mm Widefloor-standing enclosure 5 module(s): INS125, direct in 850 mm Widefloor-standing enclosure 4 module(s): INS160, direct in 850 mm Widefloor-standing enclosure 5 module(s): INS160, direct in 850 mm Widefloor-standing enclosure 4 module(s): INS40, direct in 850 mm Widefloor-standing enclosure 4 module(s): INS63, direct in 850 mm Widefloor-standing enclosure 3 module(s): modular device <= 40 A, direct in 850 mm Widefloor-standing enclosure 4 module(s): modular device, direct in 850 mm Widefloor-standing enclosure 5 module(s): NG125 without earth leakage protection , direct in 850 mm Widefloor-standing enclos 5 module(s): iC120 with earth leakage protection , direct in 850 mm Widefloor-standing enclosure 5 module(s): NG125 with earth leakage protection , direct in 850 mm Widefloor-standing enclosure
9 mm pitches	72
Quantity per set	Set of 1
Height	50 Mm
Width	488 Mm
Depth	102 Mm
Net weight	0.3 Kg
Colour	Natural
Material	Metal
Thickness	1.5 Mm

Environment

Standards	IEC 61439-1 IEC 61439-2
Product certifications	ASTA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.500 Cm
Package 1 Width	5.300 Cm
Package 1 Length	69.900 Cm
Package 1 Weight	298.000 G
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	19.000 Cm
Package 2 Width	13.000 Cm
Package 2 Length	73.500 Cm
Package 2 Weight	2.658 Kg
Unit Type of Package 3	P12
Number of Units in Package 3	240
Package 3 Height	78.800 Cm
Package 3 Width	80.000 Cm
Package 3 Length	120.000 Cm
Package 3 Weight	91.740 Kg

Offer Sustainability

REACh free of SVHC	Yes
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	Yes
Environmental Disclosure	Product Environmental Profile
Packaging made with recycled cardboard	Yes

Packaging without single use plastic	Yes
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
Halogen-free status	Halogen free plastic parts product
PVC free	Yes
Silicone-free	Yes
End of life manual availability	No need of specific recycling operations
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised