Product data sheet
Characteristics

LVS03404
Rail, PrismaSeT P, for adjustable modular device, W400mm



Main

Range	PrismaSeT
Range of product	PrismaSeT P
Product or component type	Rail
Accessory / separate part category	Installation accessory
Range compatibility	PrismaSeT PrismaSeT P
Type of rail	Modular Adjustable
Installed device	ComPact: fixed INS100 - control: direct front rotary handle - vertical installation ComPact: fixed INS160 - control: direct front rotary handle - vertical installation ComPact: fixed INS40 - control: direct front rotary handle - vertical installation ComPact: fixed INS63 - control: direct front rotary handle - vertical installation Acti 9: fixed modular device Multi9: fixed modular device Multi9: fixed NG125 without earth leakage protection - control: toggle ComPact: fixed INS125 - control: direct front rotary handle - vertical installation Acti 9: fixed modular device <= 40 A Multi9: fixed modular device <= 40 A ComPact: fixed NG160 without earth leakage protection - control: toggle ComPact: fixed NG160 NA without earth leakage protection - control: toggle ComPact: fixed NSA125...160 - control: toggle
Poles description	1 x 3P: fixed INS100 vertical installation 1 x 4P: fixed INS100 vertical installation 1 x 3P: fixed INS160 vertical installation 1 x 4P: fixed INS160 vertical installation 1 x 3P: fixed INS40 vertical installation 1 x 4P: fixed INS40 vertical installation 1 x 3P: fixed INS63 vertical installation 1 x 4P: fixed INS63 vertical installation 1 x 3P: fixed NG125 1 x 4P: fixed NG125 1 x 3P: fixed INS125 vertical installation 1 x 4P: fixed INS125 vertical installation 1 x 3P: fixed NG160 1 x 4P: fixed NG160 1 x 3P: fixed NG160 NA 1 x 4P: fixed NG160 NA 1 x 3P: fixed NSA125...160 1 x 4P: fixed NSA125...160

Complementary

Enclosure/cubicle description	Cubicle - width 400 mm depth 400 mm
Enclosure nominal height	2000 Mm
Number of vertical modules [50 mm]	4 module(s): INS100, direct in 400 mm Widecubicle 5 module(s): INS100, direct in 400 mm Widecubicle 4 module(s): INS125, direct in 400 mm Widecubicle 5 module(s): INS125, direct in 400 mm Widecubicle 4 module(s): INS160, direct in 400 mm Widecubicle 5 module(s): INS160, direct in 400 mm Widecubicle 4 module(s): INS40, direct in 400 mm Widecubicle 4 module(s): INS63, direct in 400 mm Widecubicle 3 module(s): modular device <= 40 A, direct in 400 mm Widecubicle 4 module(s): modular device, direct in 400 mm Widecubicle 5 module(s): NG125 without earth leakage protection , direct in 400 mm Widecubicle 5 module(s): NG160 without earth leakage protection , direct in 400 mm Widecubicle 5 module(s): NG160 NA without earth leakage protection , direct in 400 mm Widecubicle 5 module(s): NSA125...160, direct in 400 mm Widecubicle
9 mm pitches	20
Quantity per set	Set of 1
Height	30 Mm
Width	325 Mm
Depth	325 Mm
Net weight	0.76 Kg
Colour	Natural
Material	Metal

Environment

Standards	IEC 61439-1 IEC 61439-2
Product certifications	ASTA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.500 Cm
Package 1 Width	4.000 Cm
Package 1 Length	36.000 Cm
Package 1 Weight	728.000 G
Unit Type of Package 2	S04
Number of Units in Package 2	20
Package 2 Height	30.000 Cm
Package 2 Width	40.000 Cm
Package 2 Length	60.000 Cm
Package 2 Weight	15.650 Kg
Unit Type of Package 3	P12
Number of Units in Package 3	80
Package 3 Height	43.000 Cm
Package 3 Width	80.000 Cm
Package 3 Length	120.000 Cm
Package 3 Weight	72.240 Kg

Offer Sustainability

REACh free of SVHC	Yes
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	Yes
Environmental Disclosure	Product Environmental Profile
Packaging made with recycled cardboard	Yes

Packaging without single use plastic	Yes
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead, which is known to the S
Halogen-free status	Halogen free plastic parts product
PVC free	Yes
Silicone-free	Yes
End of life manual availability	No need of specific recycling operations
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised