
Product data sheet
Characteristics

LX4FL220
TeSys F - contactor coil - LX4FL - 220 V DC



Main

Range	TeSys
Product or component type	Contactor coil
Device short name	LX4FL
Range compatibility	TeSys TeSys F LC1F contactor
Product compatibility	LC1F630 LC1F1250
Control circuit type	DC low consumption
[Uc] control circuit voltage	220 V DC
Inductance of closed circuit	650 H
Average resistance	31 Ohm inrush at 20 °C 5160 Ohm holding at 20 °C
Operating time	40...50 ms opening 60...70 ms closing
Mechanical durability	5 Mcycles
Maximum operating rate	1200 Cyc/H 55 °C

Complementary

Coil technology	Without built-in suppressor module
Control circuit voltage limits	Drop-out: 0.2...0.35 Uc (at 55 °C) Operational: 0.85...1.1 Uc (at 55 °C)
Inrush power in W	1600 W (at 20 °C)
Hold-in power consumption in W	9 W at 20 °C

Environment

Ambient air temperature for operation	-5…55 °C
Net weight	1.45 Kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.000 Cm
Package 1 Width	11.500 Cm
Package 1 Length	22.500 Cm
Package 1 Weight	1.403 Kg
Unit Type of Package 2	S03
Number of Units in Package 2	6
Package 2 Height	30.000 Cm
Package 2 Width	30.000 Cm
Package 2 Length	40.000 Cm

Package 2 Weight	8.838 Kg
Unit Type of Package 3	P06
Number of Units in Package 3	48
Package 3 Height	75.000 Cm
Package 3 Width	80.000 Cm
Package 3 Length	60.000 Cm
Package 3 Weight	78.704 Kg

Offer Sustainability

Mercury free	Yes
Sustainable packaging	Yes
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	975ba4d0-bc82-40e2-8faa-6f6819f63b0c
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised