Product data sheet
Characteristics

MTN630419
KNX ARGUS Presence, System M, 180/2.20 m flush, polar white, Supply KNX 10 mA



Main

Range	SpaceLogic KNX
Product or component type	Presence detector
Bus type	KNX
Colour tint	Polar white
Power supply input current	10 MA

Complementary

Device presentation	Mechanism with fixing frame and cover plate
Number of channels	5
Protection type	Creep zone protection
Type of setting	Light sensitivity adjustable
Duty cycle	15300 minutes
Time delay range	0...1 s (switch-on)
Detection face	Lateral: 8 m
Detection angle	180° horizontal
Material	Plastic brilliant
Device mounting	Flush
Mounting height	2.2 M

Environment

IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.700 Cm
Package 1 Width	7.800 Cm
Package 1 Length	9.400 Cm
Package 1 Weight	92.000 G
Unit Type of Package 2	CAR
Number of Units in Package 2	30
Package 2 Height	19.700 Cm
Package 2 Width	30.800 Cm
Package 2 Length	40.400 Cm
Package 2 Weight	3.146 Kg

Offer Sustainability

Mercury free	Yes
Sustainable packaging	No
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	66b36458-2ef6-42ba-b429-8005a46f0a37
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
End of life manual availability	End Of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised