Product data sheet
Characteristics

NSYCAP223LXF
Stainless steel cover cut-out 125x125mm with filter IP55



Main

Range	ClimaSys
Product name	ClimaSys CA
Product or component type	Sealing cover
Accessory / separate part category	Thermal management accessory

Complementary

Mounting location	On enclosure
Fixing mode	By screws
Range compatibility	ClimaSys ClimaSys CV EMC fan
Device composition	1 cover 1 filter
Material	Stainless steel 304
Cut-out dimensions	223 x 223 mm
Height	External: 350 mm
Width	External: 305 mm
Depth	External : 80 mm

Environment

Product certifications	CSA
IP degree of protection	IP55

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	37.000 Cm
Package 1 Width	33.500 Cm
Package 1 Length	15.500 Cm
Package 1 Weight	3.060 Kg
Unit Type of Package 2	P12
Number of Units in Package 2	42
Package 2 Height	120.000 Cm
Package 2 Width	80.000 Cm
Package 2 Length	120.000 Cm
Package 2 Weight	143.520 Kg

Offer Sustainability

Recyclability potential, in %	8
Total lifecycle Carbon footprint	30 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	17.257453797009465
Carbon footprint of the manufacturing phase [A1 to A3]	17 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	6.064349409837378
Carbon footprint of the distribution phase [A4]	6 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.9023946802919312
Carbon footprint of the installation phase [A5]	0.9 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0
REACh free of SVHC	Yes
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	No
Carbon footprint of the end-of-life phase [C1 to C4]	5.608243187075971
Carbon footprint of the end-of-life phase [C1 to C4]	6 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	30
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
End of life manual availability	No need of specific recycling operations
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised