Product data sheet
Characteristics

NSYCMACS50
Signalling beacon adapter, square 50 mm RAL 7040. For S3CM HMI encl.



Main

Range	PanelSeT
Accessory / separate part category	Mounting accessory
Product or component type	Adaptor for signalling beacon
Device application	Multi-purpose
Enclosure nominal dimensions	-
Mounting location	On fixed brackets
Mounting support	Signalling beacon Option of passing cables through the inside For 50 mm square tube
Range compatibility	PanelSeT S3CM
Device composition	1 adaptor 1 nut
Quantity per set	Set of 1

Complementary

Material	Adaptor: aluminium
Colour	Adaptor: grey (RAL 7040)
Surface finish	Epoxy-polyester powder
Fixing mode	Direct fixing - on fixed brackets of enclosure location
Permanent permissible load	0.025 Kg
Height	0 Mm
Diameter	14 Mm
Net weight	0.11 Kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.000 Cm
Package 1 Width	9.000 Cm
Package 1 Length	10.500 Cm
Package 1 Weight	118.000 G

Offer Sustainability

REACh free of SVHC	Yes
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	No
Environmental Disclosure	Product Environmental Profile
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
End of life manual availability	No need of specific recycling operations
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised