Product data sheet
Characteristics

NSYCRS200W240V
Climasys Ultra thin resistance heater low starting current 195W 240V 400x650mm



Main

Range	ClimaSys
Product name	ClimaSys CR
Product or component type	Ultra thin resistance heater
Power range	195 W
Input voltage	240 V AC 50/60 Hz
Electrical connection	Cable length: 2 m

Complementary

Operating position	Horizontal Vertical
Ambient air temperature for operation	-60…70 °C
Temperature setting range	-40…70 °C
Material	Silicone rubber
Height	External: 380 mm
Width	External: 650 mm
Depth	External : 1.6 mm
Device composition	6 self-adhesive Velcro pads 6 plastic spacers 4 Telequick nuts 4 clip-on nuts fixing accessories
Condition of use	Air sealed enclosure Heaters must be installed with a thermal controller Electrical protection is needed
Fixing mode	By 4 screws
Mounting support	Adhesive Velcro Telequick mounting plate Standard mounting plate DIN rail

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.500 Cm
Package 1 Width	43.000 Cm
Package 1 Length	69.500 Cm
Package 1 Weight	1.130 Kg
Unit Type of Package 2	P12
Number of Units in Package 2	60
Package 2 Height	173.000 Cm

Package 2 Width	80.000 Cm
Package 2 Length	120.000 Cm
Package 2 Weight	89.300 Kg

Offer Sustainability

Recyclability potential, in %	89
Total lifecycle Carbon footprint	3 468 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	12.019984193813873
Carbon footprint of the manufacturing phase [A1 to A3]	12 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	2.239449291868051
Carbon footprint of the distribution phase [A4]	2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.10677499093783296
Carbon footprint of the installation phase [A5]	0.1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	3452.2565539368184
Carbon footprint of the use phase [B2, B3, B4, B6]	3 452 kg CO2 eq.
Mercury free	Yes
Sustainable packaging	No
Carbon footprint of the end-of-life phase [C1 to C4]	0.9875294390207687
Carbon footprint of the end-of-life phase [C1 to C4]	1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	3468
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	60bb7229-9ac3-41cb-896e-a93aa448ebf8
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead, which is known to the State
PVC free	Yes
Silicone-free	Yes
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised