Product data sheet
Characteristics

NSYCTL500DLPG
Plain front panel insulating material for DLP in PLA enclosure W500mm H146mm



Main

Range	PanelSeT
Accessory / separate part category	Enclosure accessory
Product or component type	Cover plate
Device application	Modular distribution application
Range compatibility	PanelSeT PLA PLA
Enclosure nominal dimensions	- W: 500 mm
Mounting location	On DL chassis
Device composition	2 panel

Complementary

Material	PS (polystyrene)
Colour	Grey (RAL 7035)
Fixing mode	Clipped
Type of front plate	Plain
Height	Nominal: 150 mm Real: 146 mm
Width	Nominal: 500 mm Real: 402 mm
Thickness	2 Mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.750 Cm
Package 1 Width	16.000 Cm
Package 1 Length	5.000 Cm
Package 1 Weight	250.000 G
Unit Type of Package 2	BB1
Number of Units in Package 2	2
Package 2 Height	49.500 Cm
Package 2 Width	16.000 Cm
Package 2 Length	5.000 Cm
Package 2 Weight	500.000 G

Offer Sustainability

Recyclability potential, in %	98
Total lifecycle Carbon footprint	0.4 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.217255923
Carbon footprint of the manufacturing phase [A1 to A3]	0.2 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.009624914
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.0110867
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Mercury free	Yes
Sustainable packaging	No
Carbon footprint of the end-of-life phase [C1 to C4]	0.11754238
Carbon footprint of the end-of-life phase [C1 to C4]	0.1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	1
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	9d8b9f71-75cb-4d4a-a1a2-50559a3b422a
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
End of life manual availability	No need of specific recycling operations
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised