# Product data sheet
## Characteristics

# NSYCVF38M115PF
ClimaSys forced vent. IP54, 38m3/h, 115V, with outlet grille and filter G2



## Main

| | |
|---|---|
| Range | ClimaSys |
| Product name | ClimaSys CV |
| Product or component type | Fan |
| Type of ventilation filter | Standard |
| Air flow | Free flow rate with standard filter: 38 m3/h at 50 Hz<br>Free flow rate with standard filter: 39 m3/h at 60 Hz |
| [Us] rated supply voltage | 75...125 V |
| Input voltage | 115 V 50/60 Hz |

## Complementary

| | |
|---|---|
| Power range | 3.3 W 50 Hz<br>3.5 W 60 Hz |
| [In] rated current | 0.16 A 50 Hz<br>0.16 A 60 Hz |
| Noise level | 40…41 DB |
| Bearing type | Ball |
| Height | External: 137 mm |
| Width | External: 117 mm |
| Depth | External : 49 mm |
| Cut-out dimensions | 92 x 92 mm |
| Net weight | 0.22 Kg |
| Material | Outlet grille: injected thermoplastic (ASA PC) |
| Colour | Outlet grille: grey (RAL 7035) |
| Ambient air temperature for operation | -10…70 °C |
| Ambient air temperature for storage | -40…70 °C |
| Maximum pressure | 29 Pa flow rate 0 m³/h |
| Connections - terminals | Cable |
| IP degree of protection | IP54 |
| Device composition | 1 axial motor<br>2 protective grille: on the front and rear surfaces<br>1 filter: front of axial motor<br>1 outlet grille: front<br>1 cut-out template |
| Condition of use | Outside temperature must be 5 °C lower than inside temperature<br>Flow rates depends on the work point, see ProClima software<br>Overfrequent filter replacement should be avoided<br>Surrounding environment must be relatively clean<br>Filter must be cleaned and replaced regularly |

## Packing Units

| | |
|---|---|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 7.500 Cm |
| Package 1 Width | 12.500 Cm |
| Package 1 Length | 14.500 Cm |
| Package 1 Weight | 300.000 G |
| Unit Type of Package 2 | CAR |
| Number of Units in Package 2 | 34 |
| Package 2 Height | 60.000 Cm |
| Package 2 Width | 40.000 Cm |
| Package 2 Length | 27.500 Cm |
| Package 2 Weight | 10.660 Kg |
| Unit Type of Package 3 | PAM |
| Number of Units in Package 3 | 340 |
| Package 3 Height | 80.000 Cm |
| Package 3 Width | 100.000 Cm |
| Package 3 Length | 120.000 Cm |
| Package 3 Weight | 128.000 Kg |

## Offer Sustainability

| | |
|---|---|
| Recyclability potential, in % | 64 |
| Total lifecycle Carbon footprint | 202 kg CO2 eq. |
| Carbon footprint of the manufacturing phase [A1 to A3] | 1.9482488616313047 |
| Carbon footprint of the manufacturing phase [A1 to A3] | 2 kg CO2 eq. |
| Carbon footprint of the distribution phase [A4] | 0.5945440597879781 |
| Carbon footprint of the distribution phase [A4] | 0.6 kg CO2 eq. |
| Carbon footprint of the installation phase [A5] | 0.03334014886692251 |
| Carbon footprint of the installation phase [A5] | 0 kg CO2 eq. |
| Carbon footprint of the use phase [B2, B3, B4, B6] | 198.63753094959526 |
| Carbon footprint of the use phase [B2, B3, B4, B6] | 199 kg CO2 eq. |
| Mercury free | Yes |
| Sustainable packaging | No |
| Carbon footprint of the end-of-life phase [C1 to C4] | 0.4474499010632549 |
| Carbon footprint of the end-of-life phase [C1 to C4] | 0.4 kg CO2 eq. |
| Environmental Disclosure | Product Environmental Profile |
| Total lifecycle Carbon footprint | 202 |
| Packaging made with recycled cardboard | No |
| Packaging without single use plastic | No |
| SCIP Number | 61d9d3f3-5a49-48f8-8056-1a5ad0ad4c76 |
| REACh Regulation | Reference contains Substances of Very High Concern above the threshold |
| EU RoHS Directive | Compliant By Exemption |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead, which is known to the State |
| PVC free | Yes |
| Silicone-free | Yes |
| End of life manual availability | End Of Life Information |
| Take-back | No |
| WEEE Label | The product must be disposed on European Union markets following specific waste collection and |

## Contractual warranty

| | |
|---|---|
| Warranty (in months) | 18 |

Product Life Status : Commercialised