Product data sheet
Characteristics

NSYPLA12104TG
Floor standing polyester enclosure, PanelSeT PLA, glazed door, completely sealed, 1250x1000x420mm, IP65, IK08



Main

Range	PanelSeT
Product name	PanelSeT PLA
Device application	Multi-purpose
Product or component type	Suitable enclosure
Device short name	PLA
Enclosure nominal height	1250 Mm
Enclosure nominal width	1000 Mm
Enclosure nominal depth	420 Mm
Enclosure mounting	Floor-standing
Device composition	1 top part 1 bottom part 2 side part 2 door 2 rear panel

Complementary

Body type	Sealed top and bottom part assembled with side parts
Door type	Transparent front
Number of doors	2 door(s)
Door opening side	Right and left (120 °)
Lock type	4 points lock, 5 mm double-bar
Accessibility for operation	Rear Front
Removable parts	Door by hinges Rear panel by fixing element
Material	Polyester reinforced with fibreglass
Colour	Grey (RAL 7035)
Standards	IEC 62208 UL 508 A
NEMA degree of protection	NEMA 1 NEMA 13 NEMA 2 NEMA 12
Product certifications	DNV Marine[RETURN]Veritas[RETURN]UL/cUL listed
Electrical insulation class	Class II

Environment

IP degree of protection	IP65 conforming to IEC 60529 (completely sealed)
IK degree of protection	IK08 conforming to IEC 62262 (glazed door)
Fire resistance	960 °C conforming to IEC 62208
Ambient air temperature for storage	-35…90 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	126.000 Cm
Package 1 Width	102.000 Cm
Package 1 Length	48.000 Cm
Package 1 Weight	55.500 Kg
Unit Type of Package 2	PAM
Number of Units in Package 2	2
Package 2 Height	143.000 Cm
Package 2 Width	100.000 Cm
Package 2 Length	120.000 Cm
Package 2 Weight	124.000 Kg

Offer Sustainability

Recyclability potential, in %	6
Total lifecycle Carbon footprint	432 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	201.623311250348
Carbon footprint of the manufacturing phase [A1 to A3]	202 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	110.18540894054406
Carbon footprint of the distribution phase [A4]	110 kg CO2 eq.
Carbon footprint of the installation phase [A5]	18.69653330434266
Carbon footprint of the installation phase [A5]	19 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Mercury free	Yes
Sustainable packaging	No
Carbon footprint of the end-of-life phase [C1 to C4]	101.20958509857896
Carbon footprint of the end-of-life phase [C1 to C4]	101 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	432
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	1341ad4e-77b9-40e3-bab0-32043fbc5959
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead, which is known to the State
End of life manual availability	No need of specific recycling operations
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised