Product data sheet
Characteristics

NSYPTDS4
KIT FLUSH-MOUNTING POUR ATV T4



Main

Range	PanelSeT
Product or component type	Drive flush mounting kit
Accessory / separate part category	Mounting and fixing accessory
Product specific application	Process and utilities
Range compatibility	Altivar variable speed drive ATV630[RETURN]Altivar variable speed drive ATV930[RETURN]P
NEMA size	4
Motor power kW	15 KW 220/240 V 18.5 KW 220/240 V 22 KW 220/240 V 30 KW 380/480 V 37 KW 380/480 V 45 KW 380/480 V
Mounting location	Mode 1: back of enclosure on mounting plate Mode 2: inside enclosure
Kit composition	1 x mounting plate with flanges and integrated gasket, steel with anti-corrosive coating. Fixing b 1 x fixing accessories 1 x drilling template 1 x instruction sheet 1 x edge protector profile, plastic. 1 x fan support 1 x cover for fan protection

Complementary

Permanent permissible load	28.7 Kg
Colour	Grey (RAL 7035)
Height	External: 800 mm Cut-out: 735 mm
Width	External: 385 mm Cut-out: 325 mm
Depth	Wall-enclosure separation : 151.5 mm
Net weight	8.102 Kg
Services	Configuration of enclosurepre-drilled back at requested dimensions Factory installation drive flush mounting kit on enclosure

Environment

IP degree of protection	IP55 conforming to IEC 60529

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	84.000 Cm
Package 1 Width	41.000 Cm
Package 1 Length	13.000 Cm
Package 1 Weight	8.102 Kg
Unit Type of Package 2	PAM
Number of Units in Package 2	20
Package 2 Height	146.000 Cm
Package 2 Width	100.000 Cm
Package 2 Length	120.000 Cm
Package 2 Weight	175.000 Kg

Offer Sustainability

REACh free of SVHC	Yes
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	No
Environmental Disclosure	Product Environmental Profile
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	Ba0ee14c-eebb-47d8-a070-ade906247bb0
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Cadmium and cadmium compoun
End of life manual availability	No need of specific recycling operations
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised