Product data sheet
Characteristics

NSYTRP24D
Terminal block, Linergy TR, push-in type, feed through, 2 level, 4 points, 2.5mm², grey, set of 50



Main

Range	Linergy
Product name	Linergy TR
Product or component type	Terminal block
Device short name	TRP
Accessory / separate part category	Connection accessory
Terminal block type	Passthrough
Terminal block level	2
Mounting mode	Clip-on
Nominal cross section	2.5 Mm²
Length	78 Mm
Colour	Grey
Quantity per set	Set of 50

Complementary

Width	5.2 Mm
Height	55 Mm
Connections - terminals	1 x push-in: upstream 1 x push-in: downstream
Number of terminals	2
Connection position	Inclined
Number of measurement input	4
Cable cross section	0.14…2.5 Mm², flexible without cable end 0.14…4 Mm², solid with cable end 0.2…2.5 Mm², solid without cable end 0.8…2.5 Mm², flexible with cable end
Wire stripping length	10 Mm
Tool type	Connection: without tool Disconnection: flat screwdriver
[Ue] rated operational voltage	600 V CSA[RETURN]500 V conforming to EN/IEC 60947-7-1[RETURN]440 V[RETURN]600 V
[In] rated current	20 A CSA[RETURN]20 A UL[RETURN]22 A conforming to EN/IEC 60947-7-1[RETURN]19.5 A
Material	Polyamide 6/6: insulating case Copper alloy: connector and screw Copper alloy: commoning link Chromium-nickel steel: spring
Dielectric loss	0.01 at 1 MHz conforming to IEC 60250 0.01 at 1 MHz conforming to VDE 0303-T4
Dielectric constant	3.7 at 1 MHz
Resistivity	10000 MΩ.M conforming to IEC 60093 10000 MΩ.M conforming to VDE 0303-T30

Surface resistance	1000 GΩ conforming to IEC 60093 1000 GΩ conforming to VDE 0303-T30
Creep resistance	500 CTI (> 400 kB) conforming to IEC 60093 500 CTI (> 400 kB) conforming to VDE 0303-T30
Flame retardance	V0, thickness0.8 mm conforming to UL 94
Net weight	14.3 G
Range compatibility	PrismaSeT G PrismaSeT P PrismaSet HD PrismaSeT Pack 250 PanelSeT Mureva PrismaSeT XS TeSys
Product compatibility	Spacial enclosures

Environment

Product certifications	CSA[RETURN]GL[RETURN]UL[RETURN]VDE
Dielectric strength	1000 V conforming to IEC 60243-1
Ambient air temperature for operation	-40…130 °C conforming to IEC 60216-1 -40…130 °C conforming to VDE 0304-T21

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.500 Cm
Package 1 Width	5.500 Cm
Package 1 Length	8.000 Cm
Package 1 Weight	11.000 G
Unit Type of Package 2	BB1
Number of Units in Package 2	50
Package 2 Height	6.000 Cm
Package 2 Width	9.000 Cm
Package 2 Length	27.000 Cm
Package 2 Weight	618.000 G
Unit Type of Package 3	S02
Number of Units in Package 3	400
Package 3 Height	15.000 Cm
Package 3 Width	30.000 Cm
Package 3 Length	40.000 Cm
Package 3 Weight	5.280 Kg

Offer Sustainability

Recyclability potential, in %	33
Total lifecycle Carbon footprint	5 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.072182771
Carbon footprint of the manufacturing phase [A1 to A3]	0.1 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.00151807
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.001370536
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	4.4787
REACh free of SVHC	Yes
Carbon footprint of the use phase [B2, B3, B4, B6]	4 kg CO2 eq.
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	Yes
Carbon footprint of the end-of-life phase [C1 to C4]	0.029898955

Carbon footprint of the end-of-life phase [C1 to C4]	0 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	5
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
Halogen-free status	Halogen free plastic parts product
PVC free	Yes
Silicone-free	Yes
End of life manual availability	No need of specific recycling operations
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised