
Product data sheet
Characteristics

NSYTRR24PE
Terminal block, Linergy TR, spring type, protective earth, 4 points, 2.5mm², green-yellow, set of 50



Commercial status
End of Commercialisation : SEPT 30, 2026

⚠ End of Commercialisation

Main

Range	Linergy
Product name	Linergy TR
Product or component type	Terminal block
Device short name	TRR
Terminal block type	Protective earth
Terminal block level	1
Mounting mode	Clip-on
Nominal cross section	2.5 Mm²
Length	72 Mm
Colour	Green-yellow
Quantity per set	Set of 50

Complementary

Width	5.2 Mm
Height	36.5 Mm
Connections - terminals	2 x spring terminal: downstream 2 x spring terminal: upstream
Number of terminals	4
Connection position	Top
Number of measurement input	2
Cable cross section	0.08…4 Mm², solid 0.2…2.5 Mm², flexible with cable end 0.08…2.5 Mm², flexible without cable end
Wire stripping length	10 Mm
Tool type	Connection: flat screwdriver Disconnection: flat screwdriver
Material	Polyamide 6/6: insulating case
Dielectric loss	0.01 at 1 MHz conforming to IEC 60250 0.01 at 1 MHz conforming to VDE 0303-T4
Dielectric constant	3.7 at 1 MHz
Resistivity	10000 MΩ.M conforming to IEC 60093 10000 MΩ.M conforming to VDE 0303-T30
Surface resistance	1000 GΩ conforming to IEC 60093 1000 GΩ conforming to VDE 0303-T30
Creep resistance	500 CTI (> 400 kB) conforming to IEC 60093 500 CTI (> 400 kB) conforming to VDE 0303-T30

Flame retardance	V0, thickness0.8 mm conforming to UL 94
Net weight	12.8 G
Range compatibility	PrismaSeT P PrismaSeT G PrismaSet HD PrismaSeT Pack 250 PanelSeT Mureva PrismaSeT XS TeSys
Product compatibility	Spacial enclosures

Environment

Product certifications	VDE[RETURN]DNV[RETURN]CSA[RETURN]UL[RETURN]GL
Dielectric strength	1000 V conforming to IEC 60243-1
Ambient air temperature for operation	-40…130 °C conforming to IEC 60216-1 -40…130 °C conforming to VDE 0304-T21

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.500 Cm
Package 1 Width	9.000 Cm
Package 1 Length	6.750 Cm
Package 1 Weight	13.000 G
Unit Type of Package 2	BB1
Number of Units in Package 2	50
Package 2 Height	4.500 Cm
Package 2 Width	9.000 Cm
Package 2 Length	27.000 Cm
Package 2 Weight	679.000 G
Unit Type of Package 3	S02
Number of Units in Package 3	400
Package 3 Height	15.000 Cm
Package 3 Width	30.000 Cm
Package 3 Length	40.000 Cm
Package 3 Weight	5.828 Kg

Offer Sustainability

Recyclability potential, in %	64
Total lifecycle Carbon footprint	5 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.066858914
Carbon footprint of the manufacturing phase [A1 to A3]	0.1 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.001678976
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.000936661
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	4.4787
REACh free of SVHC	Yes
Carbon footprint of the use phase [B2, B3, B4, B6]	4 kg CO2 eq.
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	Yes
Carbon footprint of the end-of-life phase [C1 to C4]	0.028765776
Carbon footprint of the end-of-life phase [C1 to C4]	0 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	5


Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
Halogen-free status	Halogen free plastic parts product
PVC free	Yes
Silicone-free	Yes
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection a

Contractual warranty

Warranty (in months)	18

Product Life Status : End of commerc. announced

NSYTRR24PE may be replaced by any of the following products:



NSYTRP24PE

Terminal block, Linergy TR, push-in type, protective earth, 4 points, 2.5mm², green-yellow, set of 50

Qty 1

Substitution date: |