
Product data sheet
Characteristics

NSYTRV22PE
Terminal block, Linergy TR, green-yellow, 2.5mm², protective earth, 2 points, Set of 50



Main

Range	Linergy
Product name	Linergy TR
Product or component type	Terminal block
Device short name	TRV
Terminal block type	Protective earth
Terminal block level	1
Mounting mode	Clip-on
Nominal cross section	2.5 Mm²
Length	47.7 Mm
Colour	Green-yellow
Quantity per set	Set of 50

Complementary

Width	5.2 Mm
Height	47.5 Mm
Connections - terminals	1 x screw terminal: upstream 1 x screw terminal: downstream
Number of terminals	2
Connection position	Sideways
Number of measurement input	2
Cable cross section	0.14…4 Mm², solid 0.2…2.5 Mm², flexible with cable end 0.14…4 Mm², flexible without cable end
Tightening torque	0.5…0.6 N.M
Wire stripping length	9 Mm
Tool type	Connection: screwdriver Disconnection: screwdriver
Material	Polyamide 6/6: insulating case
Dielectric loss	0.01 at 1 MHz conforming to IEC 60250 0.01 at 1 MHz conforming to VDE 0303-T4
Dielectric constant	3.7 at 1 MHz
Resistivity	10000 MΩ.M conforming to IEC 60093 10000 MΩ.M conforming to VDE 0303-T30
Surface resistance	1000 GΩ conforming to IEC 60093 1000 GΩ conforming to VDE 0303-T30
Creep resistance	500 CTI (> 400 kB) conforming to IEC 60093 500 CTI (> 400 kB) conforming to VDE 0303-T30
Flame retardance	V0, thickness0.8 mm conforming to UL 94
Net weight	11.58 G

Range compatibility	PrismaSeT G PrismaSeT P PrismaSeT Pack 250 PanelSeT TeSys Mureva PrismaSeT XS PrismaSet HD
Product compatibility	Spacial enclosures

Environment

Product certifications	GL[RETURN]CSA[RETURN]UL[RETURN]DNV[RETURN]VDE
Dielectric strength	1000 V conforming to IEC 60243-1
Ambient air temperature for operation	-40…130 °C conforming to IEC 60216-1 -40…130 °C conforming to VDE 0304-T21

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.700 Cm
Package 1 Width	4.800 Cm
Package 1 Length	5.000 Cm
Package 1 Weight	11.000 G
Unit Type of Package 2	BB1
Number of Units in Package 2	50
Package 2 Height	5.000 Cm
Package 2 Width	6.800 Cm
Package 2 Length	25.200 Cm
Package 2 Weight	596.000 G
Unit Type of Package 3	S03
Number of Units in Package 3	900
Package 3 Height	30.000 Cm
Package 3 Width	30.000 Cm
Package 3 Length	40.000 Cm
Package 3 Weight	11.160 Kg

Offer Sustainability

Recyclability potential, in %	64
Total lifecycle Carbon footprint	5 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.065147
Carbon footprint of the manufacturing phase [A1 to A3]	0.1 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.0015759
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.00066661
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	4.4787
Carbon footprint of the use phase [B2, B3, B4, B6]	4 kg CO2 eq.
Mercury free	Yes
Sustainable packaging	Yes
Carbon footprint of the end-of-life phase [C1 to C4]	0.029515
Carbon footprint of the end-of-life phase [C1 to C4]	0 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	5
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	8e5413ff-f1a1-4909-ad03-977097e33bd2
REACh Regulation	Reference contains Substances of Very High Concern above the threshold

EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, wh
Halogen-free status	Halogen free plastic parts product
PVC free	Yes
Silicone-free	Yes
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection a

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised