Product data sheet
Characteristics

RE7RB11MW
off-delay timing relay - 0.05..1 s - 240 V AC DC - 1OC



Commercial status
End of Commercialisation : JUN 01, 2016

⚠ End of Commercialisation

Main

Range of product	Zelio Time
Product or component type	Industrial timing relay
Component name	RE7
Time delay type	K
Time delay range	0.05 s...10 min

Complementary

Discrete output type	Relay
Contacts material	Silver with gold flashed contacts
Width pitch dimension	22.5 Mm
[Us] rated supply voltage	24...240 V AC/DC 50/60 Hz
Voltage range	0.85...1.1 Us
Connections - terminals	Screw terminals, 2 x 1.5 mm² flexible with cable end Screw terminals, 2 x 2.5 mm² flexible without cable end
Tightening torque	0.6…1.1 N.M
Setting accuracy of time delay	+/- 10 % of full scale
Repeat accuracy	+/- 0.2 %
Temperature drift	< 0.07 %/°C
Voltage drift	< 0.2 %/V
Minimum pulse duration	1 S
Reset time	50 Ms
Maximum switching voltage	250 V AC/DC
Mechanical durability	20000000 Cycles
[Ith] conventional free air thermal current	5 A
Maximum [Ie] rated operational current	2 A DC-13 24 V at 70 °C conforming to IEC 60947-5-1/1991/VDE 0660 0.1 A DC-13 250 V at 70 °C conforming to IEC 60947-5-1/1991/VDE 0660 0.2 A DC-13 115 V at 70 °C conforming to IEC 60947-5-1/1991/VDE 0660 3 A AC-15 at 70 °C conforming to IEC 60947-5-1/1991/VDE 0660
Minimum switching capacity	At 12 V 10 mA
Potentiometer characteristic	Linear 47 kOhm (+/- 20 %), 0.2 W, cable length <25 m Z1Z2 terminal(s)
Marking	CE
Overvoltage category	III conforming to IEC 60664-1
[Ui] rated insulation voltage	250 V between contact circuit and control inputs IEC certified[RETURN]250 V between contact
Supply disconnection value	> 0.1 Uc
Operating position	Any position without derating
Surge withstand	2 KV conforming to IEC 61000-4-5 level 3

Power consumption in VA	2 VA at 24 V 6 VA at 240 V 2.5 VA at 48 V 3.2 VA at 110 V
Maximum power consumption in W	1 W at 48 V 2 W at 24 V 2 W at 240 V 3.2 W at 110 V
Peak current	0.001 KA for 30 s on energisation
Terminal description	(A1-A2)CO (15-16-18)OC_OFF
Height	78 Mm
Width	22.5 Mm
Depth	80 Mm
Net weight	0.15 Kg

Environment

Immunity to microbreaks	3 Ms
Standards	EN/IEC 61812-1
Product certifications	GL[RETURN]CSA[RETURN]UL
Ambient air temperature for storage	-40…85 °C
Ambient air temperature for operation	-20…60 °C
Relative humidity	15…85 % 3K3 conforming to IEC 60721-3-3
Vibration resistance	0.35 mm (f= 10…55 Hz) conforming to IEC 60068-2-6
Shock resistance	15 gn for 11 ms conforming to IEC 60068-2-27
IP degree of protection	IP20 (terminals) IP50 (housing)
Pollution degree	3 conforming to IEC 60664-1
Dielectric strength	2.5 KV
Non-dissipating shock wave	4.8 KV
Resistance to electrostatic discharge	6 KV in contact conforming to IEC 61000-4-2 level 3 8 KV in air conforming to IEC 61000-4-2 level 3
Resistance to electromagnetic fields	10 V/M conforming to IEC 61000-4-3 level 3
Resistance to fast transients	2 KV conforming to IEC 61000-4-4 level 3
Disturbance radiated/conducted	CISPR 22 - class A CISPR 11 group 1 - class A

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Offer Sustainability

Sustainable packaging	No

Contractual warranty

Warranty (in months)	18

Product Life Status : End of commercialisation

RE7RB11MW may be replaced by any of the following products:



RE22R1KMR

single function relay, Harmony Timer Relays, 5A, 1 CO, 0.05sâ€¦10min, delay on de energization, 24...240V AC DC

Qty 1

Substitution date: |