Product data sheet
Characteristics

RM22LA32MR
level control relay, Harmony Control Relays, 8A, 2CO, 24...240V AC DC



Main

Range of product	Harmony Control Relays
Relay type	Level control relay
Product or component type	Level control relay
Relay name	RM22L
Relay monitored parameters	Detection by resistive probes
Time delay type	Adjustable 0.1...30 s, +/- 10 % of the full scale value Tt- time delay upon fault
Switching capacity in VA	2000 VA
Minimum switching current	10 MA at 5 V DC
Maximum switching current	8 A AC
Utilisation category	AC-15 conforming to IEC 60947-5-1 DC-13 conforming to IEC 60947-5-1 AC-1 conforming to IEC 60947-4-1 DC-1 conforming to IEC 60947-4-1
Contacts type and composition	2 C/O

Complementary

Maximum switching voltage	250 V AC
[Us] rated supply voltage	24...240 V AC/DC 50/60 Hz, non self-powered
Supply voltage limits	20.4…264 V AC/DC
Maximum power consumption in W	1.5 W DC
Output contacts	2 C/O
Nominal output current	8 A
Run-up delay at power-up	2.5 S 0.6 S
Maximum electrode voltage	12 V AC
Maximum electrode current	1 MA
Repeat accuracy	+/- 2 % for time delay
Measurement error	< 1 % over the whole range with voltage variation 0.05 %/°C with temperature variation
Maximum cable distance between devices	100 M between probe and delay
Sensitivity scale	0.25...5 kOhm LS (Low Sensitivity) 5...100 kOhm St (Standard Sensitivity) 50...1000 kOhm HS (High Sensitivity)
Sensitivity adjustment	5…100 %
Maximum supply current for sensors	1 MA
Cable capacitance	1 NF at HS (High Sensitivity) for probe cable 2.2 NF at St (Standard Sensitivity) for probe cable 4.7 NF at LS (Low Sensitivity) for probe cable
Overvoltage category	III conforming to IEC 60664-1
Insulation	Between supply and measurement

Connections - terminals	Screw terminals, 2 x 0.5...2 x 2.5 mm² (20 AWG...14 AWG) solid without cable end Screw terminals, 2 x 0.2...2 x 1.5 mm² (24 AWG...16 AWG) flexible with cable end Screw terminals, 1 x 0.5...1 x 3.3 mm² (20 AWG...12 AWG) solid without cable end Screw terminals, 1 x 0.2...1 x 2.5 mm² (24 AWG...14 AWG) flexible with cable end
Tightening torque	0.6…1 N.M conforming to IEC 60947-1
Housing material	Polycarbonate
Mounting support	35 mm DIN rail conforming to IEC 60715
Mounting position	Any position
Electrical durability	100000 Cycles
Mechanical durability	10000000 Cycles
Contacts material	Cadmium free
Measurement range	0.25...1000 kOhm
Safety reliability data	MTTFd = 182.6 years B10d = 170000
Width	22.5 Mm
Control type	With test button
Net weight	0.11 Kg

Environment

Immunity to microbreaks	100 Ms DC 90 Ms AC
Electromagnetic compatibility	Immunity for residential, commercial and light-industrial environments conforming to IEC 61000-6- Immunity for industrial environments conforming to IEC 61000-6-2 Emission standard for residential, commercial and light-industrial environments conforming to IEC Emission standard for industrial environments conforming to IEC 61000-6-4 Electrostatic discharge - test level: 6 kV level 3 (contact discharge) conforming to IEC 61000-4-2 Electrostatic discharge - test level: 8 kV level 3 (air discharge) conforming to IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test - test level: 10 V/m level 3 conformin Electrical fast transient/burst immunity test - test level: 4 kV level 4 (direct) conforming to IEC 610 Electrical fast transient/burst immunity test - test level: 2 kV level 4 (capacitive coupling) conformin Surge immunity test - test level: 4 kV level 4 (common mode) conforming to IEC 61000-4-5 Surge immunity test - test level: 2 kV level 4 (differential mode) conforming to IEC 61000-4-5 Conducted and radiated emissions class B group 1 conforming to CISPR 11 Conducted and radiated emissions class B conforming to CISPR 22
Standards	IEC 60255-1
Product certifications	UL[RETURN]RCM[RETURN]CSA[RETURN]GL[RETURN]CCC[RETURN]CE[RETURN]EAC
Ambient air temperature for storage	-40…70 °C
Relative humidity	93…97 % at 25…55 °C conforming to IEC 60068-2-30
Vibration resistance	0.075 mm (f= 10…58.1 Hz) not in operation conforming to IEC 60068-2-6 1 gn (f= 10…58.1 Hz) not in operation conforming to IEC 60068-2-6 0.035 mm (f= 58.1…150 Hz) in operation conforming to IEC 60068-2-6 0.5 gn (f= 58.1…150 Hz) in operation conforming to IEC 60068-2-6
Shock resistance	15 gn (duration = 11 ms) for not in operation conforming to IEC 60068-2-27 5 gn (duration = 11 ms) for in operation conforming to IEC 60068-2-27
IP degree of protection	IP20 (terminals) conforming to IEC 60529 IP40 (housing) conforming to IEC 60529 IP50 (front panel) conforming to IEC 60529
Pollution degree	3 conforming to IEC 60664-1
Dielectric test voltage	2.5 KV, 1 min AC 50 Hz conforming to IEC 60255-27

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.6 Cm
Package 1 Width	8.2 Cm
Package 1 Length	9.5 Cm
Package 1 Weight	122.0 G
Unit Type of Package 2	S02
Number of Units in Package 2	40
Package 2 Height	15 Cm
Package 2 Width	30 Cm
Package 2 Length	40 Cm
Package 2 Weight	5.492 Kg

Unit Type of Package 3	P06
Number of Units in Package 3	640
Package 3 Height	60.0 Cm
Package 3 Width	80.0 Cm
Package 3 Length	60.0 Cm
Package 3 Weight	95.14 Kg

Offer Sustainability

Recyclability potential, in %	18
Total lifecycle Carbon footprint	37 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	2.54991597524021
Carbon footprint of the manufacturing phase [A1 to A3]	3 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.0861590099613647
Carbon footprint of the distribution phase [A4]	0.1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.0007976505997106257
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	33.96586759701951
Carbon footprint of the use phase [B2, B3, B4, B6]	34 kg CO2 eq.
Mercury free	Yes
Sustainable packaging	Yes
Carbon footprint of the end-of-life phase [C1 to C4]	0.29640424549447
Carbon footprint of the end-of-life phase [C1 to C4]	0.3 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	37
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	3c095d35-159c-493c-8604-58788d456aa9
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, w
End of life manual availability	End Of Life Information
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised