Product data sheet
Characteristics

RPM11P7
plug-in relay, Harmony electromechanical relays, 15A, 1CO, lockable test button, 230V AC



Commercial status
End of Commercialisation : AUG 15, 2024

⚠ End of Commercialisation

Main

Range of product	Harmony Electromechanical Relays
Series name	Power
Product or component type	Plug-in relay
Device short name	RPM
Contacts type and composition	1 C/O
Status LED	Without
Minimum switching capacity	170 mW at 10 mA, 17 V
Reset time	20 Ms at nominal voltage
Ambient air temperature for operation	-40…55 °C
[Ithe] conventional enclosed thermal current	15 A at -40…55 °C

Complementary

[Uc] control circuit voltage	230 V AC 50/60 Hz
Control type	Lockable test button
[Ie] rated operational current	15 A at 277 V (AC) conforming to UL 15 A at 28 V (DC) conforming to UL 15 A at 250 V (AC) NO conforming to IEC 15 A at 28 V (DC) NO conforming to IEC 7.5 A at 250 V (AC) NC conforming to IEC 7.5 A at 28 V (DC) NC conforming to IEC
IP degree of protection	IP40 conforming to IEC 60529
Rated operational voltage limits	184...253 V AC
[Ui] rated insulation voltage	250 V conforming to IEC 300 V conforming to CSA 300 V conforming to UL
Maximum switching voltage	250 V conforming to IEC
Drop-out voltage threshold	>= 0.15 Uc AC
Average resistance	16270 Ohm at 20 °C +/- 15 %
Maximum switching capacity	3750 VA 420 W
Load current	15 A at 250 V AC 15 A at 28 V DC
Operating time	20 ms at nominal voltage
Mechanical durability	10000000 Cycles
Electrical durability	100000 Cycles for resistive load
Safety reliability data	B10d = 100000

Operating rate	<= 1200 cycles/hour under load <= 18000 cycles/hour no-load
Utilisation coefficient	20 %
Dielectric strength	1500 V AC between contacts with micro disconnection 2000 V AC between coil and contact with reinforced
[Uimp] rated impulse withstand voltage	4 KV during 1.2/50 µs
Protection category	RT I
Operating position	Any position
Test levels	Level A group mounting
Device presentation	Complete product
Contacts material	AgNi
Shape of pin	Flat
Net weight	0.026 Kg

Environment

Average coil consumption in VA	1.6 at 60 Hz
Pollution degree	3
Standards	CSA C22.2 No 14 IEC 61810-1 UL 508
Product certifications	UL[RETURN]EAC[RETURN]CSA
Ambient air temperature for storage	-40…85 °C
Vibration resistance	3 gn, amplitude = +/- 1 mm (f = 10…150 Hz)5 cycles in operation 5 gn, amplitude = +/- 1 mm (f = 10…150 Hz)5 cycles not operating
Shock resistance	15 gn for in operation 30 gn for not operating

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.500 Cm
Package 1 Width	2.500 Cm
Package 1 Length	4.500 Cm
Package 1 Weight	24.000 G
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	3.000 Cm
Package 2 Width	8.000 Cm
Package 2 Length	11.000 Cm
Package 2 Weight	276.000 G
Unit Type of Package 3	S01
Number of Units in Package 3	160
Package 3 Height	15.000 Cm
Package 3 Width	15.000 Cm
Package 3 Length	40.000 Cm
Package 3 Weight	4.559 Kg

Offer Sustainability

Total lifecycle Carbon footprint	16 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.2296505109
Carbon footprint of the manufacturing phase [A1 to A3]	0.2 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.003096547
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.0000781022
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	15.8199210606
REACh free of SVHC	Yes

Carbon footprint of the use phase [B2, B3, B4, B6]	16 kg CO2 eq.
Sustainable packaging	Yes
Carbon footprint of the end-of-life phase [C1 to C4]	0.003218339
Carbon footprint of the end-of-life phase [C1 to C4]	0 kg CO2 eq.
Total lifecycle Carbon footprint	16
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is k
End of life manual availability	No need of specific recycling operations

Contractual warranty

Warranty (in months)	18

Product Life Status : End of commercialisation

RPM11P7 may be replaced by any of the following products:



RPM12P7

power plug in relay, Harmony Electromechanical Relays, 15A, 1CO, with LED, with lockable test button, 230V AC

Qty 1

Substitution date: |