Product data sheet
Characteristics

RUMC31GD
universal plug in relay, Harmony Electromechanical Relays, 10A, 3CO, lockable test button, 125V DC



Commercial status
End of Commercialisation : AUG 15, 2024

⚠ End of Commercialisation

Main

Range of product	Harmony Electromechanical Relays
Series name	Universal
Product or component type	Plug-in relay
Device short name	RUM
[Uc] control circuit voltage	125 V DC
Contacts type and composition	3 C/O
Status LED	Without
Control type	Lockable test button
[Ithe] conventional enclosed thermal current	10 A at -40…55 °C

Complementary

[Uimp] rated impulse withstand voltage	4 KV (1.2/50 µs)
Minimum switching capacity	170 mW at 10 mA, 17 V
Electrical durability	100000 Cycles for resistive load
Operating time	20 ms at nominal voltage
Rated operational voltage limits	100...137.5 V DC
[Ui] rated insulation voltage	250 V conforming to IEC 300 V conforming to CSA 300 V conforming to UL
Reset time	20 Ms at nominal voltage
Maximum switching voltage	250 V conforming to IEC
Drop-out voltage threshold	>= 0.1 Uc DC
[Ie] rated operational current	10 A at 277 V AC conforming to UL 10 A at 30 V DC conforming to UL 10 A at 277 V AC (same polarity) conforming to CSA 10 A at 30 V DC conforming to CSA 5 A at 250 V AC (NC) conforming to IEC 5 A at 28 V DC (NC) conforming to IEC 10 A at 250 V AC (NO) conforming to IEC 10 A at 28 V DC (NO) conforming to IEC
Average resistance	9766 Ohm at 20 °C +/- 10 %
Maximum switching capacity	2500 VA/280 W
Mechanical durability	5000000 Cycles
Safety reliability data	B10d = 100000
Operating rate	<= 18000 cycles/hour no-load <= 1200 cycles/hour under load
Utilisation coefficient	20 %

Compatibility code	RUM
Dielectric strength	1500 V AC between contacts with micro disconnection 2500 V AC between coil and contact with reinforced 2000 V AC between poles with basic
Protection category	RT I
Pollution degree	2
Operating position	Any position
Test levels	Level A group mounting
Device presentation	Complete product
Contacts material	AgNi
Shape of pin	Cylindrical
Net weight	0.086 Kg
Average coil consumption	1.4 W
Load current	10 A at 250 V AC 10 A at 28 V DC

Environment

Ambient air temperature for operation	-40…55 °C
IP degree of protection	IP40
Standards	UL 508 IEC 61810-1 CSA C22.2 No 14
Product certifications	CSA[RETURN]UL[RETURN]EAC
Ambient air temperature for storage	-40…85 °C
Vibration resistance	3 gn, amplitude = +/- 1 mm (f = 10…150 Hz)5 cycles in operation 4 gn, amplitude = +/- 1 mm (f = 10…150 Hz)5 cycles not operating
Shock resistance	10 gn (duration = 11 ms) for in operation conforming to IEC 60068-2-27 10 gn (duration = 11 ms) for not operating conforming to IEC 60068-2-27

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.3 Cm
Package 1 Width	3.3 Cm
Package 1 Length	7.11 Cm
Package 1 Weight	0.09 Kg
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	4 Cm
Package 2 Width	14.6 Cm
Package 2 Length	19.8 Cm
Package 2 Weight	967 G
Unit Type of Package 3	S02
Number of Units in Package 3	60
Package 3 Height	15 Cm
Package 3 Width	30 Cm
Package 3 Length	40 Cm
Package 3 Weight	6.38 Kg

Offer Sustainability

Recyclability potential, in %	58
Total lifecycle Carbon footprint	21 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	4.139607509855128
Carbon footprint of the manufacturing phase [A1 to A3]	4 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.05917232491009388
Carbon footprint of the distribution phase [A4]	0.1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.014996214834259633

Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	16.47344578455447
REACh free of SVHC	Yes
Carbon footprint of the use phase [B2, B3, B4, B6]	16 kg CO2 eq.
Sustainable packaging	Yes
Carbon footprint of the end-of-life phase [C1 to C4]	0.16561735898141758
Carbon footprint of the end-of-life phase [C1 to C4]	0.2 kg CO2 eq.
Total lifecycle Carbon footprint	21
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is k
End of life manual availability	No need of specific recycling operations

Contractual warranty

Warranty (in months)	18

Product Life Status : End of commercialisation

RUMC31GD may be replaced by any of the following products:



RUMC32GD

universal plug in relay, Harmony Electromechanical Relays, 10A, 3CO, with LED, lockable test button, cylindrical, 125

Qty 1

Substitution date: |