Product data sheet
Characteristics

RXG12P7PV
interface pre assembled plug in relay with socket, Harmony Electromechanical Relays, 10A, 1CO, with LED, with lockable test button, screw, 230V AC



Main

Range of product	Harmony Electromechanical Relays
Series name	RXG series
Product or component type	Pre-assembled plug-in relay with socket
Relay type	Interface relay
Contacts type and composition	1 C/O
[Uc] control circuit voltage	230 V AC
[Ithe] conventional enclosed thermal current	10 A

Complementary

Status LED	With
Electrical durability	100000 Cycles for NO resistive load at 55 °C 100000 Cycles for NC resistive load at 55 °C
[Ui] rated insulation voltage	250 V conforming to IEC
Presentation of legend	With
Maximum switching voltage	250 V
Drop-out voltage threshold	>= 0.3 Uc AC
[Ie] rated operational current	10 A at 30 V (DC) conforming to UL 10 A at 30 V (DC) conforming to IEC 10 A at 250 V (AC) conforming to UL 10 A at 250 V (AC) conforming to IEC
Load current	10 A
Minimum switching capacity	500 mW at 100 mA, 5 V DC
Maximum switching capacity	2500 VA AC 300 W DC
Control type	Lockable test button
Average resistance	23500 Ohm at 23 °C +/- 15 %
Contact resistance	100 MOhm
Insulation resistance	1000 MOhm at 500 V DC
Electrical insulation class	Class F
Mechanical durability	10000000 Cycles
Safety reliability data	B10d = 100000
Operating rate	<= 1800 cycles/hour under load <= 18000 cycles/hour no-load
Utilisation coefficient	20 %
Operating time	20 ms
Reset time	20 Ms

Contact terminal arrangement	Separate
Connections - terminals	Connector, 1 x 0.25...1 x 2.5 mm² (22 AWG...14 AWG) flexible with cable end Connector, 2 x 0.25...2 x 1 mm² (22 AWG...17 AWG) flexible with cable end Connector, 1 x 0.5...1 x 2.5 mm² (20 AWG...14 AWG) solid without cable end Connector, 2 x 0.5...2 x 1.5 mm² (20 AWG...16 AWG) solid without cable end
Dielectric strength	1000 V AC between contacts with micro disconnection 1300 V between terminals and base with basic insulation 3000 V between terminals and LTB area with basic insulation 5000 V AC between coil and contact with reinforced insulation
[Uimp] rated impulse withstand voltage	1200 V AC between contacts with micro disconnection 6000 V between coil and contact with reinforced insulation 1500 V between terminals and case with basic insulation
Overvoltage category	III
Protection category	RT I
Pollution degree	2
Test levels	Level A group mounting
Device presentation	Complete product
Contacts material	Silver alloy (AgSnO2In2O3)
Shape of pin	Flat (faston type)
Net weight	0.058 Kg

Environment

Standards	IEC 61810-1 CSA C22.2 No 14 UL 508 IEC 61984
Product certifications	EAC[RETURN]CSA[RETURN]UL[RETURN]CE[RETURN]DNV
Ambient air temperature for storage	-40…85 °C
Ambient air temperature for operation	-40…70 °C
IP degree of protection	IP20
Relative humidity	10…85 %
Vibration resistance	3 gn, amplitude = +/- 1.5 mm (f = 10…150 Hz)in operation 5 gn, amplitude = +/- 1.5 mm (f = 10…150 Hz)not in operation

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.960 Cm
Package 1 Width	1.560 Cm
Package 1 Length	7.200 Cm
Package 1 Weight	59.000 G
Unit Type of Package 2	BB1
Number of Units in Package 2	30
Package 2 Height	17.000 Cm
Package 2 Width	17.000 Cm
Package 2 Length	27.000 Cm
Package 2 Weight	1.890 Kg
Unit Type of Package 3	S03
Number of Units in Package 3	180
Package 3 Height	30 Cm
Package 3 Width	30 Cm
Package 3 Length	40 Cm
Package 3 Weight	11.781 Kg

Offer Sustainability

Recyclability potential, in %	69
Total lifecycle Carbon footprint	13 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.4306245871
Carbon footprint of the manufacturing phase [A1 to A3]	0.4 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.0076122964
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.0003864191
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	12.1948912418
REACh free of SVHC	Yes
Carbon footprint of the use phase [B2, B3, B4, B6]	12 kg CO2 eq.
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	Yes
Carbon footprint of the end-of-life phase [C1 to C4]	0.0086758725
Carbon footprint of the end-of-life phase [C1 to C4]	0 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	13
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is k
End of life manual availability	End Of Life Information
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised