Product data sheet
Characteristics

RXG22E7
interface plug in relay, Harmony Electromechanical Relays, 5A, 2CO, with LED, lockable test button, 48V AC



Main

Range of product	Harmony Electromechanical Relays
Series name	RXG series
Product or component type	Plug-in relay
Relay type	Interface relay
Contacts type and composition	2 C/O
[Uc] control circuit voltage	48 V AC
[Ithe] conventional enclosed thermal current	5 A at -40…55 °C
Local signalling	Flag

Complementary

Status LED	With
Electrical durability	100000 Cycles for NO resistive load at 55 °C 100000 Cycles for NC resistive load at 55 °C
[Ui] rated insulation voltage	250 V conforming to IEC 300 V conforming to CSA 300 V conforming to UL
Presentation of legend	With
Maximum switching voltage	250 V AC 30 V DC
Drop-out voltage threshold	>= 0.3 Uc AC
[Ie] rated operational current	5 A at 30 V (DC) conforming to UL 5 A at 30 V (DC) conforming to IEC 5 A at 250 V (AC) conforming to UL 5 A at 250 V (AC) conforming to IEC
Load current	5 A at 250 V AC
Minimum switching capacity	50 mW at 10 mA, 5 V DC
Maximum switching capacity	1250 VA
Control type	Lockable test button
Average resistance	1100 Ohm at 23 °C +/- 10 %
Contact resistance	100 MOhm
Insulation resistance	1000 MOhm at 500 V DC
Electrical insulation class	Class F
Mechanical durability	10000000 Cycles
Safety reliability data	B10d = 100000
Operating rate	<= 1800 cycles/hour under load <= 18000 cycles/hour no-load
Utilisation coefficient	20 %
Operating time	20 ms

Reset time	20 Ms
Dielectric strength	1000 V AC between contacts with micro disconnection 5000 V AC between coil and contact with reinforced insulation 3000 V AC between poles with basic insulation 1300 V AC terminals and case with basic insulation
[Uimp] rated impulse withstand voltage	1200 V AC between contacts with micro disconnection 6000 V between coil and contact with reinforced insulation 1500 V between terminals and case with basic insulation 4000 V between poles with basic insulation
Overvoltage category	III
Protection category	RT I
Pollution degree	2
Test levels	Level A group mounting
Device presentation	Complete product
Contacts material	Silver alloy (AgSnO2In2O3)
Shape of pin	Flat (faston type)
Net weight	0.02 Kg

Environment

Standards	CSA C22.2 No 14 IEC 61810-1 UL 508
Product certifications	EAC[RETURN]CE[RETURN]UL[RETURN]CSA[RETURN]DNV
Ambient air temperature for storage	-40…85 °C
Ambient air temperature for operation	-40…70 °C
IP degree of protection	IP40
Relative humidity	10…85 %
Vibration resistance	3 gn, amplitude = +/- 0.75 mm (f = 10…150 Hz)in operation 5 gn, amplitude = +/- 0.75 mm (f = 10…150 Hz)not in operation

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.500 Cm
Package 1 Width	3.200 Cm
Package 1 Length	4.200 Cm
Package 1 Weight	21.000 G
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	3.500 Cm
Package 2 Width	8.500 Cm
Package 2 Length	9.300 Cm
Package 2 Weight	230.000 G
Unit Type of Package 3	S01
Number of Units in Package 3	200
Package 3 Height	15 Cm
Package 3 Width	15 Cm
Package 3 Length	40 Cm
Package 3 Weight	4.837 Kg

Offer Sustainability

Recyclability potential, in %	70
Total lifecycle Carbon footprint	11 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.1841355813711413
Carbon footprint of the manufacturing phase [A1 to A3]	0.2 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.06551564855924241
Carbon footprint of the distribution phase [A4]	0.1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.0007132401944399417

Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	11.13201099730464
REACh free of SVHC	Yes
Carbon footprint of the use phase [B2, B3, B4, B6]	11 kg CO2 eq.
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	Yes
Carbon footprint of the end-of-life phase [C1 to C4]	0.06466599441775461
Carbon footprint of the end-of-life phase [C1 to C4]	0.1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	11
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is k
End of life manual availability	End Of Life Information
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised