Product datasheet

Specifications



To be discontinued

standard Network Interface Module STB - DeviceNet - 125..500 kbit/s

Local distributor code:

389839264 STBNDN2212

To be discontinued on: 1 Dec 2027

To be end-of-service on: 31 Dec 2035

EAN Code: 3595862055123

Main

Range of product	Modicon STB distributed I/O solution
Product or component type	Standard Network Interface Module

Complementary

Integrated connection type	DeviceNet conforming to Open DeviceNet Vendors Assoc 5-way male 1 twisted pair (network) DeviceNet conforming to Open DeviceNet Vendors Assoc HE-13 (RS232 port) DeviceNet conforming to Open DeviceNet Vendors Assoc 8-way female (RS232 port)
Number of segments	1 primary, maximum 6 extensions
Number of server device(s)	64
Number of addressable I/O module	0…32 per island
Input current	430 mA for supply circuit
Nominal output current	0.575 A at 60…70 °C 1.2 A
Maximum output impedance	0.05 Ohm at 100000 kHz
Output voltage	5.25 V DC (tolerance: +/- 0.21 %) for logic bus
Electromagnetic compatibility	Immunity to electromagnetic interference conforming to IEC 61131-2
Transmission rate	125...500 kbit/s
Communication service	Island Bus Object (class ID101) DeviceNet Object (class ID3) Connection Object (class ID5)
Power supply type	SELV
Local signalling	1 LED green for island state (RUN) 1 LED green for MNSG 1 LED green for MNSR 1 LED green for power supply (PWR) 1 LED red for module error (ERR) 1 LED yellow for test mode
Height	40 mm
Width	128.3 mm
Depth	70 mm

Environment

IP degree of protection	IP20
Marking	CE

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product certifications	FM Class 1 Division 2 CSA UL ATEX Cat 3G C-Tick
Ambient air temperature for operation	0…60 °C without derating -25…70 °C with derating factor
Ambient air temperature for storage	-40…85 °C
Relative humidity	95 % at 60 °C without condensation
Operating altitude	<= 2000 m
Vibration resistance	3 gn (f = 58…150 Hz) on 35 mm DIN rail 5 gn (f = 58…150 Hz) on 35 mm DIN rail +/-0.35 mm (f = 10…58 Hz)
Shock resistance	30 gn for 11 ms conforming to IEC 88 reference 2-27

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.400 cm
Package 1 Width	7.200 cm
Package 1 Length	13.000 cm
Package 1 Weight	187.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	30
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	5.921 kg

Logistical informations

Country of origin	FR

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	F760fd97-89c1-4651-a374-9b8eff254b6a
EU RoHS Directive	Compliant By Exemption
REACh Regulation	Reference contains Substances of Very High Concern above the threshold

Use Again

Repack and remanufacture

Take-back	No

Dimensions Drawings

Dimensions

