Product data sheet
Characteristics

TM5SDO4R
discrete output module, Modicon TM5, 4 DO, 30V DC, 230V AC, 5A, relay, 4 changeover



Main

Range of product	Modicon TM5
Product or component type	Discrete output module
Product compatibility	PacDrive LMC Pro 2 PacDrive LMC Eco PacDrive LMC Pro
Range compatibility	PacDrive LMC motion controller
Discrete output number	4
Discrete output voltage	230 V AC (184...276 V) for relay 30 V DC (24...36 V) for relay

Complementary

Current per channel	5 A
Maximum current per output common	10 A
Mechanical durability	20000000 Cycles
Electrical durability	500000.0 Cycles 5 A
Typical current consumption	160 MA at 5 V DC
Electrical connection	Plug-in
Power dissipation in W	2.3 W
Height	99 Mm
Width	12.5 Mm
Depth	75 Mm
Net weight	0.025 Kg
Electromagnetic compatibility	Electrostatic discharge immunity test, 4 kV on contact conforming to IEC 61000-4-2 Electrostatic discharge immunity test, 8 kV in air conforming to IEC 61000-4-2 Susceptibility to electromagnetic fields, 1 V/m 2...2.7 GHz conforming to IEC 61000-4-3 Susceptibility to electromagnetic fields, 10 V/m 80...2000 MHz conforming to IEC 61000-4-3 Electrical fast transient/burst immunity test, 1 kV I/O conforming to IEC 61000-4-4 Electrical fast transient/burst immunity test, 1 kV shielded cable conforming to IEC 61000-4-4 Electrical fast transient/burst immunity test, 2 kV power lines conforming to IEC 61000-4-4 1.2/50 µs shock waves immunity test, 0.5 kV differential mode conforming to IEC 61000-4-5 1.2/50 µs shock waves immunity test, 1 kV common mode conforming to IEC 61000-4-5 Conducted RF disturbances conforming to IEC 61000-4-6 Conducted and radiated emissions conforming to CISPR 11

Environment

IP degree of protection	IP20
Marking	CE
Product certifications	CSA[RETURN]CULus[RETURN]GOST-R[RETURN]C-Tick
Standards	CSA C22.2 No 213 UL 508 IEC 61131-2 CSA C22.2 No 142
Ambient air temperature for operation	-10…55 °C without derating (horizontal installation) -10…60 °C with derating factor (horizontal installation) -10…50 °C (vertical installation)
Ambient air temperature for storage	-40…70 °C
Relative humidity	5…95 % without condensation
Operating altitude	0...2000 m
Pollution degree	2
Vibration resistance	1 gn (f = 8.4…150 Hz) on DIN rail 3.5 mm (f = 5…8.4 Hz) on DIN rail
Shock resistance	15 gn for 11 ms

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.000 Cm
Package 1 Width	6.000 Cm
Package 1 Length	10.500 Cm
Package 1 Weight	45.000 G
Unit Type of Package 2	S02
Number of Units in Package 2	97
Package 2 Height	15.000 Cm
Package 2 Width	30.000 Cm
Package 2 Length	40.000 Cm
Package 2 Weight	4.768 Kg

Offer Sustainability

Recyclability potential, in %	0
Total lifecycle Carbon footprint	94 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	1.5147801733722444
Carbon footprint of the manufacturing phase [A1 to A3]	2 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.01575621490231174
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.031078402974654234
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	92.77827318323591
REACh free of SVHC	Yes
Carbon footprint of the use phase [B2, B3, B4, B6]	93 kg CO2 eq.
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	No
Carbon footprint of the end-of-life phase [C1 to C4]	0.07178304369119706
Carbon footprint of the end-of-life phase [C1 to C4]	0.1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	94
Packaging made with recycled cardboard	No
Packaging without single use plastic	Yes
REACh Regulation	Free of Substances of Very High Concern above the threshold

EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, wh
PVC free	Yes
End of life manual availability	End Of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection a

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised