Product data sheet
Characteristics

VCCD2
Switch-disconnectors,TeSys Control,for ON/ emergency stop,40A,fixing by single hole Ø22.5mm,for mounting at back of an enclosure



Main

Range	TeSys
Product name	TeSys VARIO
Device short name	VCCD
Product or component type	Emergency stop switch disconnector

Complementary

Device composition	Handle Switch Shaft extension
Mounting support	Handle: door Switch: symmetrical rail Switch: plate
Fixing mode	Hole with 22.5 mm for handle By clips for switch By screws for switch
Performance level	High performance
Poles description	3P
Contacts type and composition	3 NO
[Ue] rated operational voltage	690 V AC 50/60 Hz
Rated operational power in W	11 KW at 690 V (AC-3) 15 KW at 690 V (AC-23A) 11 KW at 400...415 V (AC-3) 15 KW at 500 V (AC-3) 18.5 KW at 500 V (AC-23A) 5.5 KW at 230...240 V (AC-3) 7.5 KW at 230...240 V (AC-23A) 15 KW at 400...415 V (AC-23A)
[Ie] rated operational current	29 A AC-23 Ue: 400 V
[Ith] conventional free air thermal current	40 A
[Ithe] conventional enclosed thermal current	32 A
Making capacity	400 A at 400 V AC-21A 400 A at 400 V AC-22A 400 A at 400 V AC-23A
Breaking capacity	320 A at 400 V (AC-21A) 320 A at 400 V (AC-22A) 320 A at 400 V (AC-23A)
Rated conditional short-circuit current	10 KA at 400 V - associated fuse 50 A aM 10 KA at 400 V - associated fuse 50 A gG
[Icm] rated short-circuit making capacity	1 KA at 400 V at Ipeak
[Icw] rated short-time withstand current	480 A at 400 V duration: 1 s
[Uimp] rated impulse withstand voltage	8 KV

Suitability for isolation	Yes
Network type	AC DC
Intermittent duty class	30
Control type	Rotary handle
Rotary handle mounting style	Extended
Handle colour	Red
Handle front plate colour	Yellow
Rotary handle padlocking	1 to 3 padlocks 4…8 mm
Marking	0 - 1
Mechanical durability	100000 Cycles
Electrical durability	100000 Cycles AC-21 30000 Cycles DC-1...5
Connections - terminals	Power circuit: screw clamp terminals10 mm² - solid Power circuit: screw clamp terminals6 mm² - flexible - with cable end
Tightening torque	Power circuit: 2.1 N.m - on screw clamp terminals
Base dimension	60 x 60 mm
Height	74 Mm
Width	60 Mm
Net weight	0.392 Kg

Environment

Standards	IEC 60947-3
Product certifications	CSA[RETURN]UL[RETURN]GL[RETURN]CCC[RETURN]UKCA
IP degree of protection	IP20 conforming to IEC 60529 IP65
Protective treatment	TC
Mechanical robustness	Vibrations 10...150 Hz (1 gn) conforming to IEC 60068-2-6 Shocks 11 ms (30 Gn) conforming to IEC 60068-2-27
Ambient air temperature for operation	-20…50 °C
Fire resistance	960 °C conforming to IEC 60695-2-1
Compatibility code	Main switch disconnector

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.000 Cm
Package 1 Width	9.800 Cm
Package 1 Length	26.500 Cm
Package 1 Weight	346.900 G
Unit Type of Package 2	S03
Number of Units in Package 2	15
Package 2 Height	30.000 Cm
Package 2 Width	30.000 Cm
Package 2 Length	40.000 Cm
Package 2 Weight	5.702 Kg

Offer Sustainability

Recyclability potential, in %	57
Total lifecycle Carbon footprint	33 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	2.476199164519245
Carbon footprint of the manufacturing phase [A1 to A3]	2 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.07638777294859803
Carbon footprint of the distribution phase [A4]	0.1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.03436956814814385
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	28.971796700100345

Carbon footprint of the use phase [B2, B3, B4, B6]	29 kg CO2 eq.
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	Yes
Carbon footprint of the end-of-life phase [C1 to C4]	1.0395229666647516
Carbon footprint of the end-of-life phase [C1 to C4]	1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	33
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	63dc4fbe-3f44-4801-881b-22a3bb8008d9
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony tr
Halogen-free status	Halogen free product
PVC free	Yes
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection a

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised