Product datasheet

Specifications



Disconnect switch, TeSys VLS, auxiliary contact block, 1 normally closed and 1 normally open, DIN rail

VLSA11RS

EAN Code: 3606481156730

Main

Range	TeSys
Device short name	VLSA
Product or component type	Auxiliary contact block
Performance level	High performance
Contacts type and composition	1 NC + 1 NO
Contact operation	Simultaneous 1 NC Simultaneous 1 NO
Range compatibility	TeSys TeSys VARIO LS VLSA TeSys TeSys VARIO LS VLS3P TeSys TeSys VARIO LS VLS1P
Network type	DC AC
Network frequency	50/60 Hz

Complementary

Mounting location	Right Left
Main device mounting support	DIN rail
[Ue] rated operational voltage	690 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ith] conventional free air thermal current	10 A (at 55 °C)
[Ithe] conventional enclosed thermal current	10 A
[Ie] rated operational current	6 A (AC-15) at 24 V AC 6 A (AC-15) at 48 V AC 6 A (AC-15) at 127 V AC 3 A (AC-15) at 240 V AC 3 A (DC-13) at 24 V DC 1.5 A (DC-13) at 48 V DC 0.55 A (DC-13) at 127 V DC 0.27 A (DC-13) at 240 V DC
Minimum output current	10 mA
Minimum output voltage	5 V
Connections - terminals	Control circuit: screw clamp terminals2.5 mm² - flexible - without cable end
Tightening torque	Control circuit: 0.8…1 N.m - on screw clamp terminals
Height	72.6 mm
Width	9 mm
Depth	46.2 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Net weight	0.03 kg
Colour	Grey

Environment

Standards	UL 508 CSA C22.2 No 14 IEC 60947-3 IEC 60947-5
Product certifications	cULus GL
IP degree of protection	IP20 conforming to IEC 60529
Mechanical robustness	Vibrations 2...100 Hz Fc (0.7 g) conforming to IEC 60068-2-6 Shocks 11 ms Ea (15 gn) conforming to IEC 60068-2-27
Ambient air temperature for operation	-25…55 °C
Fire resistance	850 °C conforming to IEC 60695-2-11

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.000 cm
Package 1 Width	6.500 cm
Package 1 Length	8.000 cm
Package 1 Weight	37.000 g
Unit Type of Package 2	S01
Number of Units in Package 2	30
Package 2 Height	15.000 cm
Package 2 Width	15.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	1.326 kg

Logistical informations

Country of origin	IT

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**

Use Again

Repack and remanufacture

Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins**