Product data sheet
Characteristics

XALB015YC
Empty enclosure, Easy Harmony XALB, plastic, yellow lid, 1 cut out, 22mm, IP65



Main

Range of product	Easy Harmony XALB
Product or component type	Empty enclosure
Device short name	XALB
Product destination	22mm emergency functions with 1 row contact block
Control station application	Emergency push button function
Usable depth	50 Mm
Number of cut-out	1 cut-out
Colour of base of enclosure	Dark grey (RAL 7021)
Colour of cover	Yellow (RAL 1023)
Material	PC
IP degree of protection	IP65 (with XB2)
Product destination	For Ø 22 mm control and signalling units

Complementary

Assembly style	1 row contact block
Cable entry	2.0 knock-outs diameter: 20 mm at side 2.0 knock-outs diameter: 20 mm at bottom
CAD overall width	75 Mm
CAD overall height	50 Mm
CAD overall depth	75 Mm
Net weight	0.102 Kg

Environment

Ambient air temperature for storage	-40…70 °C
Ambient air temperature for operation	-25…70 °C
Electrical shock protection class	Class II conforming to IEC 60536
IK degree of protection	IK07
Standards	GB/T 14048.5 GB/T 14048.1 IEC 60947-5-1 IEC 60947-1 IEC 60947-5-4

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5 Cm
Package 1 Width	7.5 Cm
Package 1 Length	7.5 Cm
Package 1 Weight	102 G
Unit Type of Package 2	S02
Number of Units in Package 2	30
Package 2 Height	15 Cm
Package 2 Width	30 Cm
Package 2 Length	40 Cm
Package 2 Weight	3.37 Kg

Offer Sustainability

Recyclability potential, in %	18
Total lifecycle Carbon footprint	0.8 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.5364962533621729
Carbon footprint of the manufacturing phase [A1 to A3]	0.5 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.07203458209884586
Carbon footprint of the distribution phase [A4]	0.1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.00042457856448255884
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0
REACh free of SVHC	Yes
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Toxic heavy metal free	Yes
Lead free	Yes
Mercury free	Yes
Sustainable packaging	Yes
Carbon footprint of the end-of-life phase [C1 to C4]	0.2110035364370703
Carbon footprint of the end-of-life phase [C1 to C4]	0.2 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	1
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
End of life manual availability	End Of Life Information
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised