Product data sheet
Characteristics

XB2BG21C
Key selector switch, Harmony XB2, metal, black, 22mm, key no 455, 2 positions, stay put, left side pull out, 1NO



Main

Product or component type	Complete selector switch
Device presentation	Complete product
Device short name	XB2
Bezel material	Chromium plated metal
Mounting diameter	22.5 Mm
Sale per indivisible quantity	1
Head type	Standard
Operator position information	2 positions

Complementary

Fixing collar material	Zamak
CAD overall width	30 Mm
CAD overall height	40 Mm
CAD overall depth	87 Mm
Terminals description ISO n°1	(13-14)NO
Net weight	0.11 Kg
Operating position	Any position
Device mounting	Fixing hole - diameter: 22.5 mm
Fixing center	>= 30 x 40 mm (panel) - thickness: 1…6 mm
Fixing mode	Fixing screw beneath head recommended torque: 0.8 N.m Fixing screw beneath head recommended torque: 1.0 N.m
Shape of signaling unit head	Round
Type of operator	Stay put
Operator profile	Black key switch
Type of keylock	Key 455
Key withdrawal position	Left
Contacts type and composition	1 NO
Contact operation	Slow-break
Contacts usage	Standard contacts
Width	40 Mm
Height	30 Mm
Depth	87 Mm
Cap/operator or lens colour	Black
Product compatibility	ZB2..C
Mechanical durability	1000000 Cycles

Connections - terminals	Screw clamp terminal, <= 2 x 1.5 mm² with and without cable ends Screw clamp terminal, <= 1 x 2.5 mm² with and without cable ends Screw clamp terminal, >= 1 x 0.5 mm² with and without cable ends Faston terminals, connection size: 6.3 mm
Tightening torque	0.8…1.0 N.M
Shape of screw head	Cross compatible with Philips no 1 screwdriver Cross compatible with pozidriv No 1 screwdriver Slotted compatible with flat Ø 4 mm screwdriver Slotted compatible with flat Ø 5.5 mm screwdriver
Contacts material	Silver alloy (Ag/Ni)
[Ith] conventional free air thermal current	10 A conforming to IEC 60947-5-1
[Ui] rated insulation voltage	600 V (pollution degree 3) conforming to IEC 60947-1
[Uimp] rated impulse withstand voltage	6 KV conforming to IEC 60947-1
[Ie] rated operational current	3 A at 240 V, AC-15, A600 conforming to IEC 60947-5-1 0.27 A at 250 V, DC-13, Q600 conforming to IEC 60947-5-1
Electrical durability	1000000 Cycles, AC-15, 3 A at 240 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to IE 1000000 Cycles, DC-13, 0.27 A at 250 V, operating rate <3600 cyc/h, load factor: 0.5 conforming
Electrical reliability	Λ < 10exp(-6) at 5 V and 1 mA in clean environment conforming to IEC 60947-5-4 Λ < 10exp(-8) at 17 V and 5 mA in clean environment conforming to IEC 60947-5-4
Compatibility code	XB2
Customizable	No
Operator profile	Key switch
Type of operator	Stay put

Environment

Protective treatment	TC/TH
Ambient air temperature for storage	-40…70 °C
Ambient air temperature for operation	-25…70 °C
Overvoltage category	Class I conforming to IEC 60536
Standards	IEC 60947-5-1 IEC 60947-5-4 IEC 60947-1 GB/T 14048.1 GB/T 14048.5
Product certifications	CCC[RETURN]CE
IP degree of protection	IP65
IK degree of protection	IK06
Positive opening	Without
Vibration resistance	5 gn (f= 2…500 Hz) conforming to IEC 60068-2-6
Shock resistance	30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC 60068-2-27 50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27
Short-circuit protection	10 A gL fuse type gG conforming to IEC 60947-5-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.500 Cm
Package 1 Width	7.000 Cm
Package 1 Length	7.000 Cm
Package 1 Weight	120.000 G
Unit Type of Package 2	S02
Number of Units in Package 2	30
Package 2 Height	15.000 Cm
Package 2 Width	30.000 Cm
Package 2 Length	40.000 Cm
Package 2 Weight	3.880 Kg
Unit Type of Package 3	P06
Number of Units in Package 3	480
Package 3 Height	75.000 Cm
Package 3 Width	60.000 Cm

Package 3 Length	80.000 Cm
Package 3 Weight	70.080 Kg

Offer Sustainability

Recyclability potential, in %	78
Total lifecycle Carbon footprint	2 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.9145133172
Carbon footprint of the manufacturing phase [A1 to A3]	0.9 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.063842615
Carbon footprint of the distribution phase [A4]	0.1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.000263753
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0.82587
REACh free of SVHC	Yes
Carbon footprint of the use phase [B2, B3, B4, B6]	0.8 kg CO2 eq.
Mercury free	Yes
Sustainable packaging	No
Carbon footprint of the end-of-life phase [C1 to C4]	0.2888861985
Carbon footprint of the end-of-life phase [C1 to C4]	0.3 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	2
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	9e63340a-2371-4381-8f9a-5fba0ff349a4
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, w
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection a

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised