Product datasheet

Specifications



square yellow push-button Ø 16- flush spring return- 2OC

XB6ECA52F

Discontinued on: 29 Jan 2021

Discontinued

Main

Range of product	Harmony XB6E
Product or component type	Monolithic push-button
Device short name	XB6E
Bezel material	Plastic
Mounting diameter	16 mm
Sale per indivisible quantity	5
Shape of signaling unit head	Square
Type of operator	spring return
Operator profile	Yellow flush
Contacts type and composition	2 C/O
Contact operation	Snap action
Connections - terminals	Insulated faston, connection size: 2.8 x 0.5 mm Solder terminal, clamping capacity: <= 0.75 mm² AWG 19 Fast connector socket
Contacts material	Gold-flashed silver

Complementary

Net weight	0.006 kg
Overvoltage category	II conforming to IEC 60536
Operating position	Any position
Marking	CE
Mechanical durability	1000000 cycles
Tightening torque	0.6…1 N.m
Contact resistance	50 mOhm at 1/6 V
Short-circuit protection	2 A cartridge fuse type gG
[Ith] conventional free air thermal current	3 A (fast connector socket) 5 A
[Ie] rated operational current	1.5 A at 120 V, AC-12 conforming to EN/IEC 60947-5-1 1 A at 240 V, AC-12 conforming to EN/IEC 60947-5-1 0.7 A at 240 V, AC-13 conforming to EN/IEC 60947-5-1 1 A at 120 V, AC-13 conforming to EN/IEC 60947-5-1 1 A at 24 V, DC-12 conforming to EN/IEC 60947-5-1 0.7 A at 24 V, DC-13 conforming to EN/IEC 60947-5-1 0.2 A at 125 V, DC-12 conforming to EN/IEC 60947-5-1 0.15 A at 125 V, DC-13 conforming to EN/IEC 60947-5-1

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications


Electrical durability	100000 cycles, AC, 0.7 A at 220 V conforming to EN/IEC 60947-5-1 appendix C

Environment

Ambient air temperature for storage	-40…70 °C
Ambient air temperature for operation	-25…55 °C
IP degree of protection	IP40 conforming to IEC 60529
Standards	UL 508 JIS C 4520 CSA C22.2 No 14 IEC 60947-1 IEC 60947-5-1 JIS C 852
Product certifications	CCC cURus
Vibration resistance	1 mm (f= 10…55 Hz) conforming to IEC 60068-2-6
Shock resistance	10 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27

Dimensions Drawings

Square Head Pushbutton



e : panel thickness 1 to 6 mm/0.03 to 0.23 in.

(1) Nut


(2) Anti-rotation plate (thickness 0.6mm)

(3) Seal (thickness: 0.5 mm / 0.01 in.)

Mounting and Clearance

Panel Cut-out


For Square or Circular Head



Connections and Schema

Wiring Diagram

Pushbuttons and Selector Switches





Terminals 1-2 :	NC contact terminals
Terminals 1-4 :	NO contact terminals