Product data sheet
Characteristics

XESD2241
Contact block, Harmony XAC, double contact, spring return, single speed, front mounting, snap action, 3NO + 1NO



Commercial status
End of Commercialisation : APR 02, 2026

⚠ End of Commercialisation

Main

Range of product	Harmony XAC
Product or component type	Contact block
Component name	XESD
Electrical circuit type	Power circuit
Contact block application	Single speed
Contact block type	Double
Type of operator	2 spring return
Product compatibility	XACB
Mechanical interlocking	With mechanical interlocking
Contacts type and composition	3 NO + 1 NO
Poles description	3-pole
Mounting of block	Front mounting
Contact operation	Snap action Simultaneous

Complementary

Connections - terminals	Screw clamp terminals, 1 x 2.5 mm² with or without cable end Screw clamp terminals, 2 x 1.5 mm² with or without cable end
Horizontal fixing centres	40 Mm
Mechanical durability	1000000 Cycles
[Ithe] conventional enclosed thermal current	20 A
[Ui] rated insulation voltage	300 V conforming to CSA
[Uimp] rated impulse withstand voltage	6 KV conforming to IEC 60947-1
Operating force	32 N
Short-circuit protection	12 A fuse protection by cartridge fuse type aM
Rated operational power in W	3000 W AC-3 at 240 V 3000 W AC-4 at 400 V
Rated power in hp	3 Hp at 240 V
Electrical durability	1000000 Cycles AC-3, 3000 W at 400 V, operating rate <10 cyc/mn, load factor = 0.4 conformi 1000000 Cycles AC-4, 3000 W at 400 V, operating rate <10 cyc/mn, load factor = 0.4 conformi 700000 Cycles AC-3, 3000 W at 240 V, operating rate <10 cyc/mn, load factor = 0.4 conformin 700000 Cycles AC-4, 3000 W at 240 V, operating rate <10 cyc/mn, load factor = 0.4 conformin
Terminals description ISO n°1	B (33-34)NO (43-44)NO (23-24)NO (13-14)NO

Terminals description ISO n°2	(63-64)NO (44-84)NO (53-54)NO (73-74)NO B
Terminal identifier	(13-14)NO (11-12)NC
Net weight	0.21 Kg

Environment

Standards	IEC 60947-3 CSA C22.2 No 14 IEC 60947-3
Ambient air temperature for operation	-25…70 °C
Ambient air temperature for storage	-40…70 °C
Vibration resistance	15 gn (f= 10…500 Hz) conforming to IEC 60068-2-6
Shock resistance	100 gn conforming to IEC 60068-2-27
Electrical shock protection class	Class II conforming to IEC 61140

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.300 Cm
Package 1 Width	7.400 Cm
Package 1 Length	9.500 Cm
Package 1 Weight	272.000 G
Unit Type of Package 2	S02
Number of Units in Package 2	15
Package 2 Height	15.000 Cm
Package 2 Width	30.000 Cm
Package 2 Length	40.000 Cm
Package 2 Weight	4.424 Kg

Offer Sustainability

Recyclability potential, in %	46
Total lifecycle Carbon footprint	2 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	1.048040161033381
Carbon footprint of the manufacturing phase [A1 to A3]	1 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.11017053732764664
Carbon footprint of the distribution phase [A4]	0.1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.014705927613052817
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0.3095139684778404
REACh free of SVHC	Yes
Carbon footprint of the use phase [B2, B3, B4, B6]	0.3 kg CO2 eq.
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	Yes
Carbon footprint of the end-of-life phase [C1 to C4]	0.2977828966508473
Carbon footprint of the end-of-life phase [C1 to C4]	0.3 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	2
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant

California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is k
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection a

Contractual warranty

Warranty (in months)	18

Product Life Status : End of commercialisation