Product data sheet
Characteristics

XKDF12440440
joystick controller XKDF - medium hoisting w/o adaptation/potentiometer



Commercial status
End of Commercialisation : OCT 31, 2022

⚠ End of Commercialisation

Main

Range of product	Harmony XK
Product or component type	Complete joystick controller
Product specific application	Medium hoisting applications
Device short name	XKDF
Sale per indivisible quantity	1

Complementary

Bezel material	Metal
Fixing collar material	Metal
Protective treatment	TC
Type of operator	Handle mechanical to 0 position
Operator position information	All positions
Positive opening	Slow break, double-break contactswith positive opening operation
Connections - terminals	Captive screw clamp terminals, <= 2 x 1.5 mm² with cable end Captive screw clamp terminals, <= 1 x 2.5 mm² without cable end Captive screw clamp terminals, >= 1 x 0.5 mm²
Short-circuit protection	10 A cartridge fuse conforming to EN/IEC 60947-5-1
[Ith] conventional free air thermal current	10 A conforming to EN/IEC 60947-5-1 10 A conforming to CSA C22.2 No 14
[Ui] rated insulation voltage	500 V (pollution degree 3) conforming to IEC 60947-1

Environment

Ambient air temperature for storage	-40…70 °C
Ambient air temperature for operation	-20…70 °C
Overvoltage category	Class I conforming to IEC 61140
IP degree of protection	IP54 conforming to IEC 60529
Standards	EN/IEC 60947-5-1 CSA C22.2 No 14
Product certifications	EAC[RETURN]CCC[RETURN]CSA
Mechanical durability	3000000 Cycles
Vibration resistance	2 gn (f= 10…500 Hz) conforming to IEC 60068-2-6
Shock resistance	15 gn (duration = 11 ms) conforming to IEC 60068-2-27

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	0.001 G

Offer Sustainability

Sustainable packaging	No

Contractual warranty

Warranty (in months)	18

Product Life Status : End of commercialisation