Product data sheet
Characteristics

XV6C21B
Base Module, Harmony XV6, Ø60mm Modular Tower Light, 24V AC/DC base with Direct/Tube Mount Adapter, Cover Included, Dark Grey Body Color



Main

Range of product	Harmony XV6
Product or component type	Base module
Device composition	Base direct/tube & cover
Device short name	XV6
Mounting diameter	60 Mm
Electrical connection	24V
Device mounting	Direct mounting Tube mounting with fixing plate
Mounting position	Upright/Inverted
Assembly style	Up to 5 Modules (4 lens + 1 sound or 5 lens)
Material	Polycarbonate
Housing colour	Dark grey
Net weight	0.101 Kg

Complementary

[Ue] rated operational voltage	24 V AC 50/60 Hz 24 V DC
Rated operational voltage limits	21.6...26.4 V AC/DC
Electrical shock protection class	Class III
Connections - terminals	Spring clamp terminals (push 'n stay), 6 x 0.25...6 x 1.5 mm² with cable end Spring clamp terminals (push 'n stay), 6 x 0.25...6 x 1.5 mm² without cable end
Cable entry	Bottom entry
[Ui] rated insulation voltage	50 V
[Uimp] rated impulse withstand voltage	500 V

Environment

Pollution degree	2
Ambient air temperature for operation	-25…50 °C
Ambient air temperature for storage	-40…70 °C
IP degree of protection	IP65
NEMA degree of protection	UL type 12
Vibration resistance	6 gn, amplitude = +/- 0.5 mm (f = 10…500 Hz)in operation
Shock resistance	20 gn (duration = 11 ms) for in operation

Standards	UL 60947-5-1 IEC 60947-5-1 CSA C22.2 No 60947-5-1
Product certifications	cULus[RETURN]CCC[RETURN]RCM[RETURN]UKCA[RETURN]CE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.200 Cm
Package 1 Width	7.200 Cm
Package 1 Length	13.000 Cm
Package 1 Weight	125.000 G
Unit Type of Package 2	S03
Number of Units in Package 2	30
Package 2 Height	30.000 Cm
Package 2 Width	30.000 Cm
Package 2 Length	40.000 Cm
Package 2 Weight	4.237 Kg
Unit Type of Package 3	P06
Number of Units in Package 3	240
Package 3 Height	75.000 Cm
Package 3 Width	60.000 Cm
Package 3 Length	80.000 Cm
Package 3 Weight	42.500 Kg

Offer Sustainability

Recyclability potential, in %	80
Total lifecycle Carbon footprint	1 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	1.0573440032630739
Carbon footprint of the manufacturing phase [A1 to A3]	1 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.013387068366984358
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.0007541467528851152
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Mercury free	Yes
Sustainable packaging	Yes
Carbon footprint of the end-of-life phase [C1 to C4]	0.11086287671051509
Carbon footprint of the end-of-life phase [C1 to C4]	0.1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	1
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
End of life manual availability	End Of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	18

Product Life Status :	Commercialised