Product data sheet
Characteristics

XV6C21M
Base Module, Harmony XV6, Ø60mm Modular Tower Light, 100-240VAC, 120V DC base with Direct/Tube Adapter, Cover Included, Dark Grey Body Color



Main

Range of product	Harmony XV6
Product or component type	Base module
Device composition	Base direct/tube & cover
Device short name	XV6
Mounting diameter	60 Mm
Electrical connection	AC
Device mounting	Direct mounting Tube mounting with fixing plate Wall mounted
Mounting position	Upright/Inverted
Assembly style	Up to 4 Modules (3 lens + 1 sound or 4 lens)
Material	Polycarbonate
Housing colour	Dark grey
Net weight	0.199 Kg

Complementary

[Ue] rated operational voltage	100...240 V AC 50/60 Hz 120 V DC
Rated operational voltage limits	90...264 V AC
Electrical shock protection class	Class II
Connections - terminals	Spring clamp terminals (push 'n stay), 7 x 0.25...7 x 1.5 mm² with cable end Spring clamp terminals (push 'n stay), 7 x 0.25...7 x 1.5 mm² without cable end
Cable entry	Bottom or side entry
[Ui] rated insulation voltage	264 V
[Uimp] rated impulse withstand voltage	2.5 KV

Environment

Pollution degree	2
Ambient air temperature for operation	-25…50 °C
Ambient air temperature for storage	-40…70 °C
IP degree of protection	IP65
NEMA degree of protection	UL type 12
Vibration resistance	6 gn, amplitude = +/- 0.5 mm (f = 10…500 Hz)in operation
Shock resistance	20 gn (duration = 11 ms) for in operation

Standards	UL 60947-5-1 IEC 60947-5-1 CSA C22.2 No 60947-5-1
Product certifications	cULus[RETURN]CCC[RETURN]RCM[RETURN]UKCA[RETURN]CE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	18.200 Cm
Package 1 Width	7.400 Cm
Package 1 Length	7.400 Cm
Package 1 Weight	229.000 G
Unit Type of Package 2	S03
Number of Units in Package 2	15
Package 2 Height	30.000 Cm
Package 2 Width	30.000 Cm
Package 2 Length	40.000 Cm
Package 2 Weight	3.919 Kg
Unit Type of Package 3	P06
Number of Units in Package 3	120
Package 3 Height	75.000 Cm
Package 3 Width	60.000 Cm
Package 3 Length	80.000 Cm
Package 3 Weight	38.500 Kg

Offer Sustainability

Recyclability potential, in %	80
Total lifecycle Carbon footprint	10 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	2.81111077496257
Carbon footprint of the manufacturing phase [A1 to A3]	3 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.023923746699595173
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.001390193248341485
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	7.132832195374099
Carbon footprint of the use phase [B2, B3, B4, B6]	7 kg CO2 eq.
Mercury free	Yes
Sustainable packaging	Yes
Carbon footprint of the end-of-life phase [C1 to C4]	0.19547381275379935
Carbon footprint of the end-of-life phase [C1 to C4]	0.2 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	10
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
End of life manual availability	End Of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	18

Product Life Status :	Commercialised