Product data sheet
Characteristics

XV6C9V
Sound Module, Harmony XV6, Ø60mm Modular Tower Light, Programmable Vocal,Dark Grey Body Color



Main

Range of product	Harmony XV6
Product or component type	Sound module
Device composition	Editable voice alarm
Device short name	XV6
Mounting diameter	60 Mm
Signalling type	Audio sound 16 tones max
Material	Polycarbonate
Housing colour	Dark grey
Net weight	0.150 Kg
Mounting position	Upright

Complementary

Noise level	88 DB distance 1 m
Control type	External power input to select up to 16 tones
Data format	Mp3 and wav
Memory capacity	8 MB
Integrated connection type	1 USB
[Ue] rated operational voltage	24 V DC
Rated operational voltage limits	21.6...26.4 V DC
Current consumption	110 mA at 24 V DC
Inrush current	1 A
Electrical shock protection class	Class II
[Ui] rated insulation voltage	50 V
[Uimp] rated impulse withstand voltage	500 V

Environment

Pollution degree	2
Ambient air temperature for operation	-25…50 °C
Ambient air temperature for storage	-40…70 °C
IP degree of protection	IP65
NEMA degree of protection	UL type 12
Vibration resistance	6 gn, amplitude = +/- 0.5 mm (f = 10…500 Hz)in operation
Shock resistance	20 gn (duration = 11 ms) for in operation

Standards	UL 60947-5-1 IEC 60947-5-1 CSA C22.2 No 60947-5-1
Product certifications	cULus[RETURN]CCC[RETURN]RCM[RETURN]UKCA[RETURN]CE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.000 Cm
Package 1 Width	7.300 Cm
Package 1 Length	13.000 Cm
Package 1 Weight	170.000 G
Unit Type of Package 2	S03
Number of Units in Package 2	30
Package 2 Height	30.000 Cm
Package 2 Width	30.000 Cm
Package 2 Length	40.000 Cm
Package 2 Weight	5.588 Kg

Offer Sustainability

Recyclability potential, in %	80
Total lifecycle Carbon footprint	30 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	1.5072385513691056
Carbon footprint of the manufacturing phase [A1 to A3]	2 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.019083198533554637
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.0010750323979994833
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	28.02184076754111
Carbon footprint of the use phase [B2, B3, B4, B6]	28 kg CO2 eq.
Mercury free	Yes
Sustainable packaging	Yes
Carbon footprint of the end-of-life phase [C1 to C4]	0.15803447239317606
Carbon footprint of the end-of-life phase [C1 to C4]	0.2 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	30
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
End of life manual availability	End Of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised