Product data sheet
Characteristics

XVB7C9T
Sound Module, Harmony XVB7 Modular Tower Light, Ø70mm, 8 Tones, Grey



Main

Range of product	Harmony XVB7
Device composition	8 tone buzzer
Device short name	XVB7
Mounting diameter	70 Mm
Signalling type	Continuous or intermittent buzzer 8 tones
Material	Polycarbonate
Housing colour	Dark grey
Net weight	0.081 Kg
Mounting position	Upright/Inverted

Complementary

Noise level	78…102 DB at 1 m
Pulse frequency	1 Hz 20 Hz
Control type	DIP switch for tone/pulse/loudness
[Ue] rated operational voltage	24 V AC/DC
Rated operational voltage limits	21.6...26.4 V AC/DC
Current consumption	49 mA at 24 V AC 25 mA at 24 V DC
Inrush current	1 A
Electrical shock protection class	Class II
[Ui] rated insulation voltage	50 V
[Uimp] rated impulse withstand voltage	0.5 KV

Environment

Pollution degree	2
Ambient air temperature for operation	-25…60 °C
Ambient air temperature for storage	-40…70 °C
IP degree of protection	IP66
NEMA degree of protection	UL type 4X/13
Vibration resistance	6 gn, amplitude = +/- 0.5 mm (f = 10…500 Hz)in operation
Shock resistance	30 gn (duration = 6 ms) for in operation
Standards	UL 60947-5-1 IEC 60947-5-1 CSA C22.2 No 60947-5-1
Product certifications	cULus[RETURN]CCC[RETURN]RCM[RETURN]UKCA[RETURN]CE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.900 Cm
Package 1 Width	7.500 Cm
Package 1 Length	7.400 Cm
Package 1 Weight	82.000 G
Unit Type of Package 2	S03
Number of Units in Package 2	60
Package 2 Height	30.000 Cm
Package 2 Width	30.000 Cm
Package 2 Length	40.000 Cm
Package 2 Weight	5.567 Kg
Unit Type of Package 3	P06
Number of Units in Package 3	480
Package 3 Height	75.000 Cm
Package 3 Width	60.000 Cm
Package 3 Length	80.000 Cm
Package 3 Weight	51.536 Kg

Offer Sustainability

Recyclability potential, in %	87
Total lifecycle Carbon footprint	8 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	1.0860372204933506
Carbon footprint of the manufacturing phase [A1 to A3]	1 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.03149146249232426
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.0005014732177922913
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	6.368600174441161
Carbon footprint of the use phase [B2, B3, B4, B6]	6 kg CO2 eq.
Mercury free	Yes
Sustainable packaging	Yes
Carbon footprint of the end-of-life phase [C1 to C4]	0.08995452119553932
Carbon footprint of the end-of-life phase [C1 to C4]	0.1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	8
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
End of life manual availability	End Of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised