Product data sheet
Characteristics

XVEC5B6
BLUE LENS INTEGRAL FLASHING LED 24VAC/DC



Commercial status
End of Commercialisation : JUN 30, 2015

⚠ End of Commercialisation

Main

Range of product	Harmony XVE Optimum
Product or component type	Indicator bank
Beacon or indicator bank unit type	Illuminated unit
Signalling type	Flashing
Component name	XVE
Light source	Integral LED, blue
Bulb type	LED
[Us] rated supply voltage	24 V AC/DC

Complementary

Mounting diameter	70 Mm
Assembly style	Customer assembly
Connections - terminals	Screw clamp terminals, <= 1 x 1.5 mm² with cable end
Marking	CE
Short-circuit protection	0.63 A
[Ui] rated insulation voltage	250 V conforming to IEC 60947-1
Nominal voltage limit	0.85...1.1 Un conforming to IEC 60947-5-1
Current consumption	< 30 mA
[Uimp] rated impulse withstand voltage	4 KV conforming to IEC 60947-1
Luminance	800 Cd/M²
Flashing frequency	1 Hz
CAD overall width	70 Mm
CAD overall height	52 Mm
CAD overall depth	70 Mm
Net weight	0.077 Kg

Environment

Standards	EN/IEC 60947-5-1 EN/IEC 60947-1
Product certifications	CCC[RETURN]UL[RETURN]CSA
Ambient air temperature for storage	-40…70 °C
Ambient air temperature for operation	-25…55 °C
Electrical shock protection class	Class I aluminium tube mounting conforming to IEC 61140 Class I plastic tube mounting conforming to IEC 61140

Protective treatment	TC
IP degree of protection	IP40 any position except vertical position conforming to IEC 60529 IP42 vertical position conforming to IEC 60529

Offer Sustainability

Sustainable packaging	No

Contractual warranty

Warranty (in months)	18

Product Life Status : End of commercialisation

XVEC5B6 is replaced by the following product range:



61458

Ø 60 mm modular tower lights

Substitution date: |